

SASSO 60 round downlight

trim

048-2602414M 048-2696318 002-90762



Proyecto / Tipo
Notas
Cantidad / Fecha



↑ IP20 ↓ IP44	220-240V	360°	X-PERT	X-PERT
------------------	----------	------	--------	--------

General

Techo , Empotrado
rotación 360°
plata mate
Set de montaje negro intenso
delante IP44 , detrás IP20
948 lm

LED

2700 K
CRI ≥ 90
L80 / 50000 h
MacAdam inicial ≤ 2 SDCM
R _g : 99 , R _f : 91 , R ₍₁₋₁₅₎ : 89
MR 0.53
MDER 0.48

Óptico

medium
ángulo de haz 21°
UGR < 16 , ≥65° <1500 cd/m²
PstLM ≤ 1.0 ¹
SVM ≤ 0.4 ¹

Eléctrico

DALI-2
12.6 W
CP2 220-240V
75 lm/W
1 DALI Addr.

Físico


borde
diámetro 80 mm
altura 48 mm
0.27 kg

Orificio

diámetro 73 mm
espesor mín. del techo 2 mm
espesor máx. del techo 25 mm
profundidad empotrada 110 mm

¹ Valor del producto continente a plena carga (no atenuado)

Distribución luminosa



Diseño del producto



Instrucciones de montaje



Calculadora de iluminación

