

# SASSO 60 round downlight

trim

048-2602414F 048-269631G 002-90771



Proyecto / Tipo
Notas
Cantidad / Fecha



IP20 IP44	220-240V	360°	X-PERT	X-PERT
--------------	----------	------	--------	--------

## General

Techo , Empotrado
rotación 360°
plata mate
Set de montaje plateado-gris
delante IP44 , detrás IP20
988 lm

## LED

2700 K
CRI ≥ 90
L80 / 50000 h
MacAdam inicial ≤ 2 SDCM
R <sub>g</sub> : 99 , R <sub>f</sub> : 91 , R <sub>(1-15)</sub> : 89
MR 0.53
MDER 0.48

## Óptico

flood
ángulo de haz 42°
UGR < 19 , ≥ 65° < 1500 cd/m²
PstLM ≤ 1.0 <sup>1</sup>
SVM ≤ 0.4 <sup>1</sup>

## Eléctrico

non atenuable
12.6 W
CP2 220-240V
78 lm/W

## Físico


borde
diámetro 80 mm
altura 48 mm
0.21 kg

## Orificio

diámetro 73 mm
espesor mín. del techo 2 mm
espesor máx. del techo 25 mm
profundidad empotrada 60 mm

<sup>1</sup> Valor del producto continente a plena carga (no atenuado)

## Distribución luminosa



## Diseño del producto



## Instrucciones de montaje



## Calculadora de iluminación

