

SASSO 60 round downlight

trimless

048-2602514M 048-2696117 002-90762



Proyecto / Tipo	
Notas	
Cantidad / Fecha	



↑ IP20 ↓ IP44	220-240V	↻	X-PERT	X-PERT
------------------	----------	---	--------	--------

General

Techo , Empotrado
rotación 360°
plata mate
Set de montaje blanco tráfico
delante IP44 , detrás IP20
1010 lm

LED

3000 K
CRI ≥ 90
L80 / 50000 h
MacAdam inicial ≤ 2 SDCM
R _g : 100 , R _f : 91 , R _{f(1-5)} : 88
MR 0.59
MDER 0.53

Óptico

medium
ángulo de haz 21°
UGR < 16 , ≥65° <1500 cd/m²
PstLM ≤ 1.0 ¹
SVM ≤ 0.4 ¹

Eléctrico

DALI-2
12.6 W
CP2 220-240V
80 lm/W
1 DALI Addr.

Físico


sin borde
diámetro 73 mm
altura 48 mm
0.28 kg

Orificio


diámetro 73 mm
profundidad empotrada 120 mm

¹ Valor del producto continente a plena carga (no atenuado)

Distribución luminosa



Diseño del producto



Instrucciones de montaje



Calculadora de iluminación

