

SASSO 60 round downlight

trim

048-2602414S 048-2696318 002-90771



| |
|------------------|
| Proyecto / Tipo |
| Notas |
| Cantidad / Fecha |



| | | | | |
|------------------|----------|------|--------|--------|
| ↑ IP20 ↓ IP44 | 220-240V | 360° | X-PERT | X-PERT |
|------------------|----------|------|--------|--------|

General

| |
|------------------------------|
| Techo , Empotrado |
| rotación 360° |
| plata mate |
| Set de montaje negro intenso |
| delante IP44 , detrás IP20 |
| 567 lm |

LED

| |
|---|
| 2700 K |
| CRI ≥ 90 |
| MacAdam inicial ≤ 3 SDCM |
| R _g : 99 , R _r : 91 , R _{t(1-15)} : 89 |
| MR 0.53 |
| MDER 0.48 |

Óptico

| |
|-------------------------------|
| spot |
| ángulo de haz 12° |
| UGR < 16 , ≥ 65° < 1500 cd/m² |
| PstLM ≤ 1.0 ¹ |
| SVM ≤ 0.4 ¹ |

Eléctrico

| |
|---------------|
| non atenuable |
| 13.1 W |
| CP2 220-240V |
| 43 lm/W |

Físico


| |
|----------------|
| borde |
| diámetro 80 mm |
| altura 48 mm |
| 0.21 kg |

Orificio

| |
|------------------------------|
| diámetro 73 mm |
| espesor mín. del techo 2 mm |
| espesor máx. del techo 25 mm |
| profundidad empotrada 60 mm |

¹ Valor del producto continente a plena carga (no atenuado)

Distribución luminosa



Diseño del producto



Instrucciones de montaje



Calculadora de iluminación

