



# MINO CIRCLE

ceiling


**EN** Ring shaped luminaire housing from rolled aluminium extruded profile, seamlessly welded; surface powder coated; light inset consisting of highly reflective coated die-cast aluminium for improved thermal management; HPO (High Performance Opal) cover for uniform illumination; micro prismatic PMMA diffuser incl. diffuser film for homogeneous illumination and reduced luminance; sound absorbing elements available; energy-efficient LEDs with very good colour rendering

**ES** Luminaria con forma de anillo fabricada en aluminio con soldadura de alta calidad; superficie con recubrimiento de pintura en polvo; elemento de luz formado por fundación de aluminio con acabado altamente reflectante para una gestión térmica mejorada; difusor opal de alta calidad que proporciona una iluminación uniforme; cubierta microprismática de PMMA con lámina difusora para la reducción de iluminancia y un alumbrado homogéneo; elementos de absorción acústica disponibles; LEDs de alta eficiencia que proporcionan una alta reproducción cromática

## Quickinfo

3000K, 4000K  
 CRI ≥ 80, 3 SDCM  
 up to 123lm/W  
 L90 @ 50 000h  
 DALI-2  
 opal, microprismatic

## Types




## Luminaire colours



## Light distribution



DiiA® standards  
 251, 252, 253



## Order options

<b>COLOUR TEMPERATURE</b>	☐☐
3000K	5
4000K	6

### CONTROL

DALI-2

### MATERIAL COLOUR

☐ pure white RAL 9010	7
● white aluminium RAL 9006	G
● jet black RAL 9005	8
● special colours	X

### LIGHT OPTIC COVER

opal high performance	H
microprismatic	Z


## Options on request

### COLOUR RENDERING INDEX


CRI ≥ 90

### CONTROL

Casambi




## MINO 60 CIRCLE 1000 ceiling




### DIRECT

SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
65 W	3000 K	7130 lm	0 3 4 - 2 1 1 2 ☐☐☐☐
	4000 K	7550 lm	




## MINO 60 CIRCLE 1500 ceiling




### DIRECT

SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
99 W	3000 K	11400 lm	0 3 4 - 2 1 1 0 ☐☐☐☐
	4000 K	12100 lm	




## MINO 60 CIRCLE 3000 ceiling




### DIRECT

SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
198 W	3000 K	23000 lm	0 3 4 - 2 1 1 4 ☐☐☐☐ 3 7 H
	4000 K	24300 lm	

other configurations see MINO 60 CURVE system



## MINO 60 CIRCLE 6000 ceiling



### DIRECT

SYSTEM POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
396 W	3000 K	45900 lm	0 3 4 - 2 1 1 6 ☐☐☐☐ 3 7 H
	4000 K	48600 lm	

other configurations see MINO 60 CURVE system

## Acoustic elements

see page 608