



TWIST 100 2 lamps

recessed


EN Round recessed spotlight in die-cast aluminium; powder coated; installation without tools in mounting set with ball catch system; with trim; double lamps; 360° rotatable and 45° tiltable outward; COB (Chip on Board) technology for maximum efficiency; no multiple shadows; energy-efficient LEDs with very good colour rendering; high quality reflector with spherical facet finish; precise radiation characteristic

ES Proyector empotrable redondo de inyección en aluminio; recubierto de polvo; instalación sin herramientas mediante kit de montaje con sistema inserción de bola; con marco; con dos luces; giratorio 360° y orientable 45°; Chip on Board que proporciona una máxima eficiencia; sin formación de sombras; LEDS de alta eficiencia que proporcionan una alta reproducción cromática; reflector alta calidad con óptica de bisel esférica; característica proyección precisa

Quickinfo

3000 K, 3500 K, 4000 K
CRI $\geq$ 90 / 2 SDCM
hasta 141 lm/W
L80 / 50000 h
DALI-2, non atenuable
front IP20, back IP20

Types



Color



Set de montaje




Distribución luminosa



360° rotatable,
45° tiltable



TWIST 100 trim 2 lamps



SPOT CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	FIXTURE	ORDER CODE
2x22.7 W, 650 mA	3000 K	2x3100 lm	136 lm/W	0 4 8 - 1 1 2 1 0 1 ☒ S
	3500 K	2x3140 lm	138 lm/W	0 4 8 - 1 1 2 1 2 1 ☒ S
	4000 K	2x3140 lm	138 lm/W	0 4 8 - 1 1 2 1 1 1 ☒ S




MEDIUM CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	FIXTURE	ORDER CODE
2x22.7 W, 650 mA	3000 K	2x3150 lm	139 lm/W	0 4 8 - 1 1 2 1 0 1 ☒ M
	3500 K	2x3190 lm	140 lm/W	0 4 8 - 1 1 2 1 2 1 ☒ M
	4000 K	2x3200 lm	141 lm/W	0 4 8 - 1 1 2 1 1 1 ☒ M

FLOOD CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	FIXTURE	ORDER CODE
2x22.7 W, 650 mA	3000 K	2x3110 lm	137 lm/W	0 4 8 - 1 1 2 1 0 1 ☒ F
	3500 K	2x3150 lm	138 lm/W	0 4 8 - 1 1 2 1 2 1 ☒ F
	4000 K	2x3160 lm	139 lm/W	0 4 8 - 1 1 2 1 1 1 ☒ F


Planning Information



2 optical accessories can be combined

Electrical mounting accessories (optional)

THROUGH WIRING CONNECTION BOX




TYPE	L-W-H (mm)	ORDER CODE
non DIM cable ø 4 – 12 mm	105-58-30	0 0 5 - 2 5 3 1 1 1 0
DALI cable ø 4 – 12 mm	105-58-30	0 0 5 - 2 5 5 1 1 1 0

Linect®-Ready

Mounting accessories (required)

MOUNTING SET with trim 2 lamps for intermediate ceilings, 2-25 mm



COLOUR	L-W-H (mm)	ORDER CODE
traffic white	218-118-35	0 4 8 - 2 7 9 8 3 1 7
jet black	218-118-35	0 4 8 - 2 7 9 8 3 1 8

Order options

COLOUR	
traffic white RAL 9016	☒ 7
jet black RAL 9005	☒ 8


Electrical accessories (required)

POWER SUPPLY 650 mA, PC2, -264 V AC

TYPE	INPUT VOLTAGE	EFFICIENCY	L-W-H (mm)	ORDER CODE
31 W non DIM	198 V AC	η 88 %	143-43-30	0 0 2 - 9 0 7 8 0
28 W DALI-2	176 V AC	η 85 %	143-43-30	0 0 2 - 9 0 7 8 9

Optical accessories (optional)

HONEYCOMB LOUVER



Ø-H (mm)	ORDER CODE
75-9	0 8 0 - 6 4 0 1 1 1 8



LINEAR PRISMATIC LENS

Ø-H (mm)	ORDER CODE
75-9	0 8 0 - 6 4 0 2 1 1 0 P



SNOOT angle

Ø-H (mm)	ORDER CODE
66-38	0 8 0 - 6 4 0 3 3 1 8



SNOOT medium

Ø-H (mm)	ORDER CODE
66-38	0 8 0 - 6 4 0 3 2 1 8



SNOOT short

Ø-H (mm)	ORDER CODE
66-23	0 8 0 - 6 4 0 3 1 1 8