



LENO

trimless


EN Low profile recessed channel; suitable for trimless installation in 12.5mm plasterboard ceilings; suitable for wall or ceiling mounting; surface powder coated; special edge design with grooves for better adhesion of filler; easy mounting without need to cut the substructure; fall-safe light inset made of extruded aluminium profile, can be inserted in the canal without tools by magnetic holders; side coupled light, directed downwards by LGP body (Light Guiding Prism) and highly efficient reflector; homogeneously illuminated, satinised (flush or jut-out) or microprismatic PMMA cover; optional with asymmetric light distribution; energy-efficient LEDs with very good colour rendering; incl. external converter for ceiling insertion

ES Canal para montaje empotrado extremadamente plano; apropiado para montaje sin borde en techos de escayola de 12,5 mm; apropiado para el montaje en la pared y en el techo; superficie con recubrimiento de pintura en polvo; formación de bordes especial con aletas para mejor adherencia de la masilla; montaje sencillo sin cortar la construcción inferior; elemento de luz asegurado contra caídas de perfil de aluminio extrusionado que se puede introducir en el canal sin herramientas por medio de un soporte magnético; fuente de luz insertada en un lateral que es guiada y reflectada a través de unos prismas y reflector de alta calidad; cubierta de PMMA iluminada homogéneamente, satinada (enrasada o sobresaliente) o micro-prismática; opcional con distribución asimétrica; LEDS de alta eficiencia que proporcionan una alta reproducción cromática; incl. convertidor externo para inserción en el techo

Quickinfo

3000 K, 4000 K
CRI $\geq$ 80 / 3 SDCM
UGR $\leq$ 19
hasta 2,130 lm/m
hasta 137 lm/W
L90 / 50000 h
DALI-2
Asymmetric Wallwasher, High Performance Opal, Jut-Out, Microprismatic
IP40, back IP20

Types



Color



Distribución luminosa



DiiA® standards
251, 252, 253




system solution



microprismatic
UGR $\leq$ 19




quick
installation



LENO trimless



MICROPRISMATIC CRI ≥ 80, DALI-2, traffic white



SYSTEM	LENGTH	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
10.8 W	616 mm	3000 K	1160 lm	107 lm/W	0 5 1 - 8 3 1 2 5 3 7 G
		4000 K	1230 lm	114 lm/W	0 5 1 - 8 3 1 2 6 3 7 G
19.1 W	1224 mm	3000 K	2320 lm	121 lm/W	0 5 1 - 8 3 1 4 5 3 7 G
		4000 K	2450 lm	128 lm/W	0 5 1 - 8 3 1 4 6 3 7 G
28.6 W	1833 mm	3000 K	3480 lm	122 lm/W	0 5 1 - 8 3 1 6 5 3 7 G
		4000 K	3680 lm	129 lm/W	0 5 1 - 8 3 1 6 6 3 7 G
38.0 W	2441 mm	3000 K	4630 lm	122 lm/W	0 5 1 - 8 3 1 8 5 3 7 G
		4000 K	4910 lm	129 lm/W	0 5 1 - 8 3 1 8 6 3 7 G

OPAL CRI ≥ 80, DALI-2, traffic white

SYSTEM	LENGTH	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
10.8 W	616 mm	3000 K	1220 lm	113 lm/W	0 5 1 - 8 3 1 2 5 3 7 H
		4000 K	1300 lm	120 lm/W	0 5 1 - 8 3 1 2 6 3 7 H
19.1 W	1224 mm	3000 K	2450 lm	128 lm/W	0 5 1 - 8 3 1 4 5 3 7 H
		4000 K	2590 lm	136 lm/W	0 5 1 - 8 3 1 4 6 3 7 H
28.6 W	1833 mm	3000 K	3670 lm	128 lm/W	0 5 1 - 8 3 1 6 5 3 7 H
		4000 K	3890 lm	136 lm/W	0 5 1 - 8 3 1 6 6 3 7 H
38.0 W	2441 mm	3000 K	4900 lm	129 lm/W	0 5 1 - 8 3 1 8 5 3 7 H
		4000 K	5190 lm	137 lm/W	0 5 1 - 8 3 1 8 6 3 7 H



OPAL JUT-OUT CRI ≥ 80, DALI-2, traffic white

SYSTEM	LENGTH	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
10.8 W	616 mm	3000 K	1170 lm	108 lm/W	0 5 1 - 8 3 1 2 5 3 7 J
		4000 K	1240 lm	115 lm/W	0 5 1 - 8 3 1 2 6 3 7 J
19.1 W	1224 mm	3000 K	2350 lm	123 lm/W	0 5 1 - 8 3 1 4 5 3 7 J
		4000 K	2490 lm	130 lm/W	0 5 1 - 8 3 1 4 6 3 7 J
28.6 W	1833 mm	3000 K	3520 lm	123 lm/W	0 5 1 - 8 3 1 6 5 3 7 J
		4000 K	3730 lm	130 lm/W	0 5 1 - 8 3 1 6 6 3 7 J
38.0 W	2441 mm	3000 K	4700 lm	124 lm/W	0 5 1 - 8 3 1 8 5 3 7 J
		4000 K	4970 lm	131 lm/W	0 5 1 - 8 3 1 8 6 3 7 J

ASYMMETRIC CRI ≥ 80, DALI-2, traffic white

SYSTEM	LENGTH	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
15.6 W	616 mm	3000 K	1570 lm	101 lm/W	0 5 1 - 8 3 1 2 5 3 7 A
		4000 K	1660 lm	106 lm/W	0 5 1 - 8 3 1 2 6 3 7 A
31.0 W	1224 mm	3000 K	3140 lm	101 lm/W	0 5 1 - 8 3 1 4 5 3 7 A
		4000 K	3320 lm	107 lm/W	0 5 1 - 8 3 1 4 6 3 7 A
47.0 W	1833 mm	3000 K	4710 lm	100 lm/W	0 5 1 - 8 3 1 6 5 3 7 A
		4000 K	4990 lm	106 lm/W	0 5 1 - 8 3 1 6 6 3 7 A
62.0 W	2441 mm	3000 K	6280 lm	101 lm/W	0 5 1 - 8 3 1 8 5 3 7 A
		4000 K	6650 lm	107 lm/W	0 5 1 - 8 3 1 8 6 3 7 A

Planning Information



LENO trimless, microprismatic,
19.1W, 4000K

ROOM VALUES	
Room dimensions	5.4 × 4 × 2.8m
Reflection factor	0.7 0.5 0.2
Maintenance factor	0.8

CALCULATION SURFACE	
Surface dimensions	1.6 × 0.8
Surface height	0.75
Average illuminance (E _m)	> 500 lx
Uniformity (U ₀)	> 0.6

GLARE EVALUATION	
Table Classification X=4H Y=8H S=0.25H	
UGR transversal	≤19
UGR axial	≤19

Mounting accessories (optional)

DISMOUNTING TOOL

TYPE	ORDER CODE
vacuum cup	0 8 6 - 3 0 0 0 0

Jungheinrich Hauptverwaltung

Austria

Arquitecto
reichardt+partner
architekten

Fotografía
walter schießwohl



Productos utilizados



LENO trimless



LENO trim system





Donau Versicherung AG Insurance Group, Vienna

Austria

Arquitecto
RAHU Architekten ZT
KG


Fotografía
DONAU Versicherung/
Thomas Pitterle



Productos utilizados



LENO trimless




COMBO trim




**MINO 60 CIRCLE
suspended**



**SASSO 100 round
adjustable recessed
1 lamp**



**SASSO 100 round
downlight recessed 1
lamp**



**SASSO 100 round
wallwasher recessed
1 lamp**



**SASSO 100 round
wallwasher/floor
recessed 1 lamp**



