



LENO

semi-recessed


EN Low profile recessed mounted luminaire, 15 mm visible height; suitable for wall or ceiling mounting; suitable for installation in primed or exposed concrete, in plasterboard constructions and in plastered walls or ceilings; surface powder coated; fall-safe light inset made of extruded aluminium profile, can be inserted in the canal without tools by magnetic holders; side coupled light, directed downwards by LGP body (Light Guiding Prism) and highly efficient reflector; homogeneously illuminated, satinised (flush or jut-out) or microprismatic PMMA cover; energy-efficient LEDs with very good colour rendering

ES Lámpara empotrable extremadamente plana con altura visible de 15 mm; apropiado para el montaje en la pared y en el techo; apropiada para el montaje en hormigón alisado u hormigón visto, en construcciones de placas de yeso y en paredes o techos enlucidos; superficie con recubrimiento de pintura en polvo; elemento de luz asegurado contra caídas de perfil de aluminio extrusionado que se puede introducir en el canal sin herramientas por medio de un soporte magnético; fuente de luz insertada en un lateral que es guiada y reflectada a través de unos prismas y reflector de alta calidad; cubierta de PMMA iluminada homogéneamente, satinada (enrasada o sobresaliente) o micro-prismática; LEDs de alta eficiencia que proporcionan una alta reproducción cromática

Quickinfo

3000 K, 4000 K
 CRI $\geq$ 80 / 3 SDCM
 UGR $\leq$ 19
 hasta 2,130 lm/m
 hasta 137 lm/W
 L90 / 50000 h
 DALI-2
 High Performance Opal, Jut-Out, Microprismatic
 IP40, back IP20

Types



Color




Distribución luminosa



DiiA® standards
 251, 252, 253




system solution



microprismatic
 UGR $\leq$ 19



quick
 installation




LENOR semi-recessed



MICROPRISMATIC CRI ≥ 80, DALI-2

SYSTEM	LENGTH	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
10.8 W	618 mm	3000 K	1160 lm	107 lm/W	0 5 1 - 8 5 1 2 5 3 ☒ G
		4000 K	1230 lm	114 lm/W	0 5 1 - 8 5 1 2 6 3 ☒ G
19.1 W	1226 mm	3000 K	2320 lm	121 lm/W	0 5 1 - 8 5 1 4 5 3 ☒ G
		4000 K	2450 lm	128 lm/W	0 5 1 - 8 5 1 4 6 3 ☒ G
28.6 W	1835 mm	3000 K	3480 lm	122 lm/W	0 5 1 - 8 5 1 6 5 3 ☒ G
		4000 K	3680 lm	129 lm/W	0 5 1 - 8 5 1 6 6 3 ☒ G
38.0 W	2443 mm	3000 K	4630 lm	122 lm/W	0 5 1 - 8 5 1 8 5 3 ☒ G
		4000 K	4910 lm	129 lm/W	0 5 1 - 8 5 1 8 6 3 ☒ G




OPAL CRI ≥ 80, DALI-2

SYSTEM	LENGTH	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
10.8 W	618 mm	3000 K	1220 lm	113 lm/W	0 5 1 - 8 5 1 2 5 3 ☒ H
		4000 K	1300 lm	120 lm/W	0 5 1 - 8 5 1 2 6 3 ☒ H
19.1 W	1226 mm	3000 K	2450 lm	128 lm/W	0 5 1 - 8 5 1 4 5 3 ☒ H
		4000 K	2590 lm	136 lm/W	0 5 1 - 8 5 1 4 6 3 ☒ H
28.6 W	1835 mm	3000 K	3670 lm	128 lm/W	0 5 1 - 8 5 1 6 5 3 ☒ H
		4000 K	3890 lm	136 lm/W	0 5 1 - 8 5 1 6 6 3 ☒ H
38.0 W	2443 mm	3000 K	4900 lm	129 lm/W	0 5 1 - 8 5 1 8 5 3 ☒ H
		4000 K	5190 lm	137 lm/W	0 5 1 - 8 5 1 8 6 3 ☒ H

OPAL JUT-OUT CRI ≥ 80, DALI-2

SYSTEM	LENGTH	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
10.8 W	618 mm	3000 K	1170 lm	108 lm/W	0 5 1 - 8 5 1 2 5 3 ☒ J
		4000 K	1240 lm	115 lm/W	0 5 1 - 8 5 1 2 6 3 ☒ J
19.1 W	1226 mm	3000 K	2350 lm	123 lm/W	0 5 1 - 8 5 1 4 5 3 ☒ J
		4000 K	2490 lm	130 lm/W	0 5 1 - 8 5 1 4 6 3 ☒ J
28.6 W	1835 mm	3000 K	3520 lm	123 lm/W	0 5 1 - 8 5 1 6 5 3 ☒ J
		4000 K	3730 lm	130 lm/W	0 5 1 - 8 5 1 6 6 3 ☒ J
38.0 W	2443 mm	3000 K	4700 lm	124 lm/W	0 5 1 - 8 5 1 8 5 3 ☒ J
		4000 K	4970 lm	131 lm/W	0 5 1 - 8 5 1 8 6 3 ☒ J

Planning Information



LENOR semi-recessed, 19.1W, 4000K

ROOM VALUES


Room dimensions	5.4 × 4 × 2.8 m
Reflection factor	0.7 0.5 0.2
Maintenance factor	0.8

CALCULATION SURFACE

Surface dimensions	1.6 × 0.8
Surface height	0.75
Average illuminance (E _m)	> 500 lx
Uniformity (U ₀)	> 0.6

GLARE EVALUATION

Table Classification X=4H Y=8H S=0.25H	
UGR transversal	≤ 19
UGR axial	≤ 19



Order options

COLOUR

pure white RAL 9010	☒ 7
jet black RAL 9005	☒ 8

Mounting accessories (optional)

DISMOUNTING TOOL

TYPE	ORDER CODE
vacuum cup	0 8 6 - 3 0 0 0 0