



## FRAME 40

recessed with trim


<sup>EN</sup> Luminaire housing made of extruded aluminium; recessed luminaire with trim; suitable for ceiling thickness of 8-25 mm; surface powder coated; luminaire profile can be pre-mounted; remaining luminaire components mounted without tools; light inset consisting of highly reflective coated extruded profile for improved thermal management; HPO (High Performance Opal) cover for uniform illumination; energy-efficient LEDs with very good colour rendering

<sup>ES</sup> Cuerpo de lámpara de perfil extrusionado de aluminio; luminaria empotrable con marco; apropiada para grosores de techo entre 8-25 mm; superficie con recubrimiento de pintura en polvo; perfil de luminaria premontable; resto de componentes luminosos montables sin herramienta; elemento de luz formado por perfil extruido con acabado altamente reflectante para una gestión térmica mejorada; difusor opal de alta calidad que proporciona una iluminación uniforme; LEDS de alta eficiencia que proporcionan una alta reproducción cromática

### Quickinfo

3000 K, 4000 K  
CRI ≥ 90, 3 SDCM  
up to 116 lm/W  
L90 @ 50 000 h  
DALI-2  
opal

### Types

recessed trim 



### Colours



### Light distribution




opal




DiiA® standards  
251, 252, 253



system  
solution



tunable white  
2700–6500 K



CRI ≥ 98  
XPECTRUM

Order options

COLOUR TEMPERATURE	
3000K	0
4000K	1

CONTROL
DALI-2

MATERIAL COLOUR	
<input type="radio"/> traffic white RAL 9016	7
<input checked="" type="radio"/> white aluminium RAL 9006	G
<input type="radio"/> jet black RAL 9005	8

LIGHT OPTIC COVER
opal high performance

Options on request


COLOUR RENDERING INDEX
CRI ≥ 98 XPECTRUM

COLOUR TEMPERATURE
tunable white 2700–6500K
DALI-2 DT8

LIGHT OPTIC COVER
microprismatic



FRAME 40 trim



MID LUMEN

SYS. POWER	COLOUR TEMP.	LUM. FLUX	L (mm)	ORDER CODE
12.4W	3000K	1370lm	1019	0 4 2 - 7 1 1 2 :: 3 H
	4000K	1430lm		
24.8W	3000K	2730lm	2019	0 4 2 - 7 1 1 4 :: 3 H
	4000K	2860lm		
37W	3000K	4100lm	3019	0 4 2 - 7 1 1 6 :: 3 H
	4000K	4300lm		

HIGH LUMEN

SYS. POWER	COLOUR TEMP.	LUM. FLUX	L (mm)	ORDER CODE
20.1W	3000K	2140lm	1019	0 4 2 - 7 1 2 2 :: 3 H
	4000K	2240lm		
40W	3000K	4270lm	2019	0 4 2 - 7 1 2 4 :: 3 H
	4000K	4470lm		
60W	3000K	6410lm	3019	0 4 2 - 7 1 2 6 :: 3 H
	4000K	6710lm		

Mounting accessories

CONCRETE INSTALLATION HOUSING

L (mm)	W-H (mm)	ORDER CODE
1038	57-87	0 4 2 - 7 1 9 5 2 1 0
2038	57-87	0 4 2 - 7 1 9 5 4 1 0
3038	57-87	0 4 2 - 7 1 9 5 6 1 0

