

BETO

suspended

EN Luminaire housing from extruded aluminium profile, angular design; extremely slim design (only 42x42 mm); no visible screws; surface powder coated; pendant fitting with cable suspension; with integrated tool-less suspension height adjustment; spring clip attachment to the luminaire; freely positionable; with transparent feeder cable; extruded profile for improved thermal management; high-gloss reflector with faceted design; direct/indirect light distribution; indirect light component with integrated PC boards and high-quality lens system for maximum, homogeneous ceiling illumination, optionally separately controllable; energy-efficient LEDs with very good colour rendering


ES Cuerpo de perfil de aluminio con diseño angular; forma extremadamente esbelta (solo 42x42 mm); sin tornillos visibles; superficie con recubrimiento de pintura en polvo; suspendido con cable; regulación de la altura sin necesidad de herramientas; fijación en las lámparas por medio de enganches elásticos; ajustable de una manera sencilla; incl. cable de alimentación transparente; perfil extruido para una mejor gestión del calor; reflector de alto brillo con óptica facetada; característica de emisión directa/indirecta; componente de luz indirecta con pletinas propias y una óptica de lente de alta calidad para una claridad de techo máxima y homogénea, opcionalmente dotada de control independiente; LEDS de alta eficiencia que proporcionan una alta reproducción cromática

Quickinfo

3000 K, 4000 K, TW
 CRI ≥ 80, 3 SDCM
 UGR ≤ 16 / 65° ≤ 1500 cd/m²
 up to 148 lm/W
 L90 @ 50 000 h
 DALI-2, DALI-2 sensor
 reflector (UGR ≤ 16)

Types

BETO suspended



Colours






Light distributions



DiiA® standards
 251, 252, 253



UGR ≤ 19



Order options

COLOUR TEMPERATURE

3000 K	5
4000 K	6
tunable white 2700–6500 K*	

*DALI-2 DT8

3000 K + TW 2700–6500 K*	
4000 K + TW 2700–6500 K*	

*DALI-2 DT8 (separately controllable)

CONTROL

DALI-2	3
DALI-2 D/I separately control.*	4
DALI-2 sensor	7

*not for tunable white 1857 mm;
not for indirect power

MATERIAL COLOUR

○ pure white RAL 9010	7
● jet black RAL 9005	8

LIGHT OPTIC COLOUR

chrome reflector	R
black reflector	B

LIGHT OPTIC COVER

reflector (UGR ≤ 16)

Options on request

COLOUR RENDERING INDEX

CRI ≥ 90	
CRI ≥ 98 XPECTRUM	




CONTROL

Casambi

TUNABLE WHITE

direct light static 3000 K or
4000 K and indirect light
tunable 2700–6500 K

BETO suspended




INDIRECT POWER

SYS. POWER	COLOUR TEMP.	LUM. FLUX	L (mm)	ORDER CODE
56 W	3000 K	↑ 7360 lm	3457	0 7 4 - 6 2 N 9
	4000 K	↑ 8120 lm		
63 W	2700–6500 K	↑ 7640 lm	3457	0 7 4 - 6 2 N 9 D

DIRECT / INDIRECT POWER

SYS. POWER	COLOUR TEMP.	LUM. FLUX	L (mm)	ORDER CODE
50 W	3000 K	↓ 3250 / ↑ 3460 lm	1857	0 7 4 - 6 2 4 6
	4000 K	↓ 3580 / ↑ 3810 lm		
54 W	3000 K	↓ 3350 lm	1857	0 7 4 - 6 2 D 6 5 4
(2 × DALI)	2700–6500 K	↑ 3120 lm		
54 W	4000 K	↓ 3540 lm	1857	0 7 4 - 6 2 D 6 6 4
(2 × DALI)	2700–6500 K	↑ 3120 lm		
56 W (2 ×)	2700–6500 K	↑ 7030 lm	1857	0 7 4 - 6 2 4 6 D
88 W	3000 K	↓ 4870 / ↑ 6910 lm	3057	0 7 4 - 6 2 4 9
	4000 K	↓ 5370 / ↑ 7630 lm		
90 W	3000 K	↓ 5020 lm	3057	0 7 4 - 6 2 D 9 5 4
(2 × DALI)	2700–6500 K	↑ 6240 lm		
90 W	4000 K	↓ 5310 lm	3057	0 7 4 - 6 2 D 9 6 4
(2 × DALI)	2700–6500 K	↑ 6240 lm		
93 W (2 ×)	2700–6500 K	↑ 12250 lm	3057	0 7 4 - 6 2 4 9 D

Technical data



BETO suspended, 88 W, 4000 K
direct/indirect power

ROOM VALUES

Room dimensions	5.4 × 4 × 2.8 m
Reflection factor	0.7 0.5 0.2
Maintenance factor	0.8
Mounting height	2.25 m


CALCULATION SURFACE

Surface dimensions	1.6 × 0.8
Surface height	0.75
Average illuminance (E _m)	> 500 lx
Uniformity (U ₀)	> 0.6

GLARE EVALUATION

Table Classification X=4H Y=8H S=0.25H	
UGR transversal	≤ 19
UGR axial	≤ 19
65° < 1500 cd/m²	

Light distribution



reflector (UGR ≤ 16)
direct/indirect power

LUMINOUS FLUX value calculated for
CRI ≥ 80, colour white, reflector chrome;
reflector black -29 %