




Quickinfo

6500 K
DALI-2 ESSENTIAL sensor, DALI-2
SENSE sensor
front IP20, IP40, back IP20

Types



Color



Set de montaje



SASSO 60 round sensor / emergency

EN Round inset (Emergency Light or Sensor); installation without tools in mounting set (trimless or with trim); surface lacquered; installation possible in different housings; LED emergency light inset: 3 variants with different test possibilities - Basic with test button, selftest with status LED or Pro DALI with monitoring via DALI; sensor with DALI-2 control: 2 variants - Basic with brightness and presence sensor or Pro with additional temperature, humidity, air quality and noise level measurement


ES Inserto redondo (luz emergencia/sensor); instalación sin herramientas mediante kit de montaje (con o sin marco); superficie lacada; posibilidad de instalar distintas carcasas; inserto luz de emerg. LED: 3 variantes con difer. opciones de test - Basic con botón de prueba, autotest con LED de estado o Pro DALI con superv. a través de DALI; sensor con control DALI-2: 2 variantes - Basic con sensor de luminosidad y presencia o Pro con medición adic. de temperatura, humedad y calidad del aire y nivel de ruido



SASSO 60 round sensor essential




COLOUR		ORDER CODE
jet black		0 4 8 - 2 6 9 3 1 1 1
traffic white		0 4 8 - 2 6 9 3 1 1 7



SASSO 60 round sensor sense



COLOUR		ORDER CODE
jet black		0 4 8 - 2 6 9 3 1 2 1
traffic white		0 4 8 - 2 6 9 3 1 2 7




SASSO 60 round emergency light



3H | BASIC | SPOT LENS / ESCAPE ROUTE LENS / ANTI PANIC LENS CRI ≥ 80

SYSTEM	COLOUR TEMP.	LUM. FLUX	ORDER CODE
1.0 W	6500 K	217 lm	0 4 8 - 2 6 9 3 2 1 ☒

incl. 3 interchangeable lenses



3H | SELFTEST | SPOT LENS / ESCAPE ROUTE LENS / ANTI PANIC LENS CRI ≥ 80

SYSTEM	COLOUR TEMP.	LUM. FLUX	ORDER CODE
1.0 W	6500 K	217 lm	0 4 8 - 2 6 9 3 2 2 ☒

incl. 3 interchangeable lenses

3H | PRO | SPOT LENS / ESCAPE ROUTE LENS / ANTI PANIC LENS CRI ≥ 80


SYSTEM	COLOUR TEMP.	LUM. FLUX	ORDER CODE
1.0 W	6500 K	217 lm	0 4 8 - 2 6 9 3 2 3 ☒

incl. 3 interchangeable lenses


Order options

COLOUR		☒
jet black	RAL 9005	1
traffic white	RAL 9016	7


Mounting accessories (required)




MOUNTING SET trimless			
TYPE	COLOUR	Ø·H (mm)	ORDER CODE
for plasterboard ceilings 12.5/15/25 mm	traffic white	73·29	0 4 8 - 2 6 9 6 1 1 7
for SASSO 60 round SPIO 60 downlight			



MOUNTING SET trimless for soft acoustic ceilings			
COLOUR	CEILING THICKNESS	Ø·H (mm)	ORDER CODE
traffic white	25-40 mm	80·25	0 4 8 - 2 6 9 6 1 9 7




MOUNTING SET with trim 1 lamp for intermediate ceilings, 2-25 mm			
COLOUR	Ø·H (mm)	ORDER CODE	
traffic white	80·40	0 4 8 - 2 6 9 6 3 1 7	
jet black	80·40	0 4 8 - 2 6 9 6 3 1 8	




MOUNTING SET with trim for soft acoustic ceilings 25-40 mm			
COLOUR	Ø·H (mm)	ORDER CODE	
traffic white	80·27	0 4 8 - 2 6 9 6 3 9 7	
jet black	80·27	0 4 8 - 2 6 9 6 3 9 8	


Mounting accessories (optional)



EXPOSED CONCRETE MOUNTING HOUSING		
COLOUR	L·W·H (mm)	ORDER CODE
white aluminium	230·230·162	0 4 8 - 2 6 9 5 2 1 0



MOUNTING TOOL			
TYPE	COLOUR	L·W·H (mm)	ORDER CODE
for soft acoustic ceilings	traffic black	77·77·35	0 4 8 - 2 6 9 5 9 1 8



PRIMED CONCRETE MOUNTING HOUSING	
L-W-H (mm)	ORDER CODE
614-307-120	0 4 8 - 2 6 9 5 1 1 0
order mounting set separately	

Electrical accessories (optional)

REPLACEMENT ACCUPACK

TYPE	ORDER CODE
3h battery life	0 4 8 - 2 6 9 3 9 1 0