

Quickinfo

2700 K, 3000 K, 4000 K, colour
warm dimming 1800 K - 2700 K
CRI ≥ 90 , CRI ≥ 95 / 2 SDCM, 3
SDCM, 4 SDCM
UGR ≤ 10 , UGR ≤ 19
hasta 93 lm/W
L80 / 50000 h, L85 / 50000 h,
L90 / 50000 h
DALI-2, non attenuable
front IP20

Types

trim		83
		98
trimless		83
		80

Color



Set de montaje



Distribución luminosa



SASSO PRO 80 adjustable offset round

recessed

EN Round recessed spotlight in die-cast aluminium; installation without tools in mounting set (trimless or with trim) with ball catch system; surface powder coated; light inset rotatable and tiltable; offset lighting level; optical attachments available as accessories; with optional high-quality lens system with precise radiation characteristic; and high-quality reflector with spherical facet effect design, precise radiation characteristic with two different beam angles; installed and exchanged without tools; COB (Chip on Board) technology or high power LEDs for maximum efficiency; no multiple shadows; efficient LEDs with very good colour rendering

ES Proyector empotrable redondo de inyección en aluminio; instalación sin herramientas mediante kit de montaje (con o sin marco) con sistema inserción de bola; superficie con recubrimiento de pintura en polvo; elemento de luz girable e inclinable; offset; los accesorios ópticos están disponibles como accesorios; opcionalmente con sistema óptico de lentes de alta calidad con precisa característica de emisión; o bien reflector de alta calidad con óptica facetada esférica, precisa característica de emisión con dos diferentes ángulos de emisión; intercambiable sin herramienta; con tecnología COB (Chip on Board) o LEDs de alta potencia para proporcionar una máxima eficiencia; no sombras múltiples; LEDs de eficiencia que proporcionan una alta reproducción cromática




DiiA® standards
251, 252, 253



rotatable 360°,
tiltable 35°



Colour Warm
Dimming 1800
- 2700 K



SASSO PRO 80 adjustable



SUPER SPOT CRI ≥ 90, non DIM

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
7.6 W	2700 K	388 lm	51 lm/W	0 4 8 - 2 3 1 0 4 1 ☒ V
7.7 W	3000 K	379 lm	49 lm/W	0 4 8 - 2 3 1 0 5 1 ☒ V
	4000 K	408 lm	53 lm/W	0 4 8 - 2 3 1 0 6 1 ☒ V


MEDIUM

SYSTEM	COLOUR TEMP.	CRI ≥	LUM. FLUX	SYSTEM	ORDER CODE
6.5 W	CWD	95	377 lm	58 lm/W	0 4 8 - 2 3 1 0 E 3 ☒ M
8.3 W	2700 K	90	721 lm	87 lm/W	0 4 8 - 2 3 1 0 4 1 ☒ M
	3000 K	90	757 lm	91 lm/W	0 4 8 - 2 3 1 0 5 1 ☒ M
	4000 K	90	765 lm	92 lm/W	0 4 8 - 2 3 1 0 6 1 ☒ M
12.2 W	2700 K	90	1010 lm	83 lm/W	0 4 8 - 2 3 1 2 4 ☒ M
	3000 K	90	1050 lm	86 lm/W	0 4 8 - 2 3 1 2 5 ☒ M
	4000 K	90	1120 lm	92 lm/W	0 4 8 - 2 3 1 2 6 ☒ M

FLOOD CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
8.3 W	2700 K	728 lm	88 lm/W	0 4 8 - 2 3 1 0 4 1 ☒ F
	3000 K	765 lm	92 lm/W	0 4 8 - 2 3 1 0 5 1 ☒ F
	4000 K	773 lm	93 lm/W	0 4 8 - 2 3 1 0 6 1 ☒ F
12.2 W	2700 K	1020 lm	84 lm/W	0 4 8 - 2 3 1 2 4 ☒ F
	3000 K	1060 lm	87 lm/W	0 4 8 - 2 3 1 2 5 ☒ F
	4000 K	1130 lm	93 lm/W	0 4 8 - 2 3 1 2 6 ☒ F

Electrical mounting accessories (optional)




THROUGH WIRING CONNECTION BOX

TYPE	L-W-H (mm)	ORDER CODE
non DIM cable ø 4 – 12 mm	105-58-30	0 0 5 - 2 5 3 1 1 1 0
DALI cable ø 4 – 12 mm	105-58-30	0 0 5 - 2 5 5 1 1 1 0


Linect®-Ready

Mounting accessories (required)



MOUNTING SET trimless for installation in plasterboard ceilings 12.5/15/25 mm

COLOUR	L-W-H (mm)	ORDER CODE
traffic white	124-92-33	0 5 2 - 1 9 3 1 3 2 7
jet black	124-92-33	0 5 2 - 1 9 3 1 3 2 8




MOUNTING SET with trim for intermediate ceilings, 5-25 mm

COLOUR	Ø-H (mm)	ORDER CODE
traffic white	98-43	0 5 2 - 1 9 3 2 3 2 7
jet black	98-43	0 5 2 - 1 9 3 2 3 2 8

Order options

CONTROL		COLOUR	
non DIM	1	traffic white RAL 9016	7
DALI-2	3	jet black RAL 9005	8



Mounting accessories (optional)

PRIMED CONCRETE MOUNTING HOUSING

L·W·H (mm)	ORDER CODE
240·400·130	0 5 2 - 1 9 1 4 3 2 0
order mounting set separately	

Optical accessories (optional)



HONEYCOMB LOUVER

COLOUR	Ø·H (mm)	ORDER CODE
traffic white	54·11	0 4 8 - 2 0 9 1 3 1 7
jet black	54·11	0 4 8 - 2 0 9 1 3 1 8

LINEAR PRISMATIC LENS

COLOUR	Ø·H (mm)	ORDER CODE
traffic white	54·11	0 4 8 - 2 0 9 2 3 1 7
jet black	54·11	0 4 8 - 2 0 9 2 3 1 8



SNOOT

COLOUR	Ø·H (mm)	ORDER CODE
traffic white	54·25	0 4 8 - 2 0 9 1 1 1 7
jet black	54·25	0 4 8 - 2 0 9 1 1 1 8



SNOOT WITH HONEYCOMB LOUVER

COLOUR	Ø·H (mm)	ORDER CODE
traffic white	54·25	0 4 8 - 2 0 9 1 2 1 7
jet black	54·25	0 4 8 - 2 0 9 1 2 1 8