

SASSO PRO 100 adjustable flush round recessed


EN Round recessed spotlight in die-cast aluminium; installation without tools in mounting set (trimless or with trim) with ball catch system; surface powder coated; installation possible in different housings; light inset rotatable and tiltable; optical attachments as accessories; high-quality reflector with spherical facet effect design, precise radiation characteristics with different beam angles; installed and exchanged without tools; COB (Chip on Board) technology for maximum efficiency; no multiple shadows; efficient LEDs with very good colour rendering

ES Proyector empotrable redondo de inyección en aluminio; instalación sin herramientas mediante kit de montaje (con o sin marco) con sistema inserción de bola; superficie con recubrimiento de pintura en polvo; posibilidad de instalar distintas carcasas; elemento de luz girable e inclinable; los accesorios ópticos como accesorios; bien reflector de alta calidad con óptica facetada esférica, precisa característica de emisión con diferentes ángulos de emisión; intercambiable sin herramienta; Chip on Board que proporciona una máxima eficiencia; no proporciona sombras múltiples; LEDS de eficiencia que proporcionan una alta reproducción cromática

Quickinfo

2700 K, 3000 K, 4000 K, colour warm dimming 2000 K - 3000 K, tunable white 1800 K - 3000 K, tunable white 2700 K - 6500 K
CRI $\geq$ 90, CRI $\geq$ 92, CRI $\geq$ 95 / 3
SDCM, 4 SDCM
UGR $\leq$ 19
hasta 105 lm/W
L80 / 50000 h, L85 / 50000 h, L90 / 50000 h
DALI-2, non atenuable
front IP20

Types



Color




Set de montaje



Distribución luminosa




DiiA® standards
251, 252, 253





rotatable 360°,
tiltable 35°




Colour Warm
Dimming 2000
– 3000 K



tunable white
1800 – 3000 K
or 2700 – 6500
K



SASSO PRO 100 adjustable



SPOT COB, CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
14.7 W	2700 K	1350 lm	92 lm/W	0 4 8 - 2 4 1 0 4 S
	3000 K	1410 lm	96 lm/W	0 4 8 - 2 4 1 0 5 S
	4000 K	1490 lm	101 lm/W	0 4 8 - 2 4 1 0 6 S
27.0 W	2700 K	2170 lm	80 lm/W	0 4 8 - 2 4 1 2 4 S
	3000 K	2270 lm	84 lm/W	0 4 8 - 2 4 1 2 5 S
	4000 K	2400 lm	89 lm/W	0 4 8 - 2 4 1 2 6 S

MEDIUM CRI ≥ 90

SYSTEM	COLOUR TEMP.	ILLUMINANT	LUM. FLUX	SYSTEM	ORDER CODE
14.7 W	2700 K	COB	1350 lm	92 lm/W	0 4 8 - 2 4 1 0 4 M
	3000 K	COB	1410 lm	96 lm/W	0 4 8 - 2 4 1 0 5 M
	4000 K	COB	1490 lm	101 lm/W	0 4 8 - 2 4 1 0 6 M
27.0 W	2700 K	COB	2170 lm	80 lm/W	0 4 8 - 2 4 1 2 4 M
	3000 K	COB	2270 lm	84 lm/W	0 4 8 - 2 4 1 2 5 M
		COB HO	2790 lm	103 lm/W	0 4 8 - 2 4 1 3 5 M
	4000 K	COB	2400 lm	89 lm/W	0 4 8 - 2 4 1 2 6 M
		COB HO	2820 lm	104 lm/W	0 4 8 - 2 4 1 3 6 M

FLOOD

SYSTEM	COLOUR TEMP.	ILLUMINANT	CRI ≥	LUM. FLUX	SYSTEM	ORDER CODE
14.7 W	2700 K	COB	90	1360 lm	93 lm/W	0 4 8 - 2 4 1 0 4 F
	3000 K	COB	90	1420 lm	97 lm/W	0 4 8 - 2 4 1 0 5 F
	4000 K	COB	90	1500 lm	102 lm/W	0 4 8 - 2 4 1 0 6 F
14.9 W	CWD	COB	95	853 lm	57 lm/W	0 4 8 - 2 4 1 1 E 3 F
27.0 W	2700 K	COB	90	2190 lm	81 lm/W	0 4 8 - 2 4 1 2 4 F
	3000 K	COB	90	2280 lm	84 lm/W	0 4 8 - 2 4 1 2 5 F
		COB HO	90	2810 lm	104 lm/W	0 4 8 - 2 4 1 3 5 F
	4000 K	COB	90	2420 lm	90 lm/W	0 4 8 - 2 4 1 2 6 F
		COB HO	90	2840 lm	105 lm/W	0 4 8 - 2 4 1 3 6 F

WIDE FLOOD cob LED, CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
14.7 W	2700 K	1280 lm	87 lm/W	0 4 8 - 2 4 1 0 4 W
	3000 K	1340 lm	91 lm/W	0 4 8 - 2 4 1 0 5 W
	4000 K	1420 lm	97 lm/W	0 4 8 - 2 4 1 0 6 W
27.0 W	2700 K	2070 lm	77 lm/W	0 4 8 - 2 4 1 2 4 W
	3000 K	2160 lm	80 lm/W	0 4 8 - 2 4 1 2 5 W
	4000 K	2280 lm	84 lm/W	0 4 8 - 2 4 1 2 6 W

Order options

CONTROL		COLOUR	
non DIM	1	traffic white RAL 9016	7
DALI-2	3	jet black RAL 9005	8



SASSO PRO 100 adjustable (TW 2700K - 6500K)



FLOOD DALI-2, COB, CRI ≥ 92

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
27.7 W	tunable w.	2210 lm	80 lm/W	0 4 8 - 2 4 1 2 D 3 ☒ F



SASSO PRO 100 adjustable (TW 1800K - 3000K)



FLOOD DALI-2, cob LED, CRI ≥ 92

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
29.7 W	tunable w.	1830 lm	62 lm/W	0 4 8 - 2 4 1 2 L 3 ☒ F

Electrical mounting accessories (optional)

THROUGH WIRING CONNECTION BOX


TYPE	L-W-H (mm)	ORDER CODE
non DIM cable ø 4 – 12 mm	105-58-30	0 0 5 - 2 5 3 1 1 1 0
DALI cable ø 4 – 12 mm	105-58-30	0 0 5 - 2 5 5 1 1 1 0

Linect®-Ready

Mounting accessories (required)


MOUNTING SET trimless

TYPE	L-W-H (mm)	ORDER CODE
for installation in plasterboard ceilings 12.5/15/25 mm	149-113-33	0 5 2 - 1 9 2 1 4 4 7



MOUNTING SET with trim for intermediate ceilings, 5-25 mm

COLOUR	Ø-H (mm)	ORDER CODE
traffic white	112-43	0 5 2 - 1 9 2 2 4 4 7
jet black	112-43	0 5 2 - 1 9 2 2 4 4 8



Mounting accessories (optional)

EXPOSED CONCRETE MOUNTING HOUSING

L-W-H (mm)	ORDER CODE
229-227-160	0 5 2 - 1 9 1 3 4 1 0

Order options

COLOUR	
traffic white RAL 9016	☒ 7
jet black RAL 9005	8

PRIMED CONCRETE MOUNTING HOUSING**L·W·H (mm)**
240·400·130

order mounting set separately

ORDER CODE

0 5 2 - 1 9 1 4 4 2 0

Optical accessories (optional)**HONEYCOMB LOUVER**

COLOUR	Ø·H (mm)	ORDER CODE
traffic white	74·11	0 4 8 - 2 1 9 1 3 1 7
jet black	74·11	0 4 8 - 2 1 9 1 3 1 8

LINEAR PRISMATIC LENS

COLOUR	Ø·H (mm)	ORDER CODE
traffic white	74·11	0 4 8 - 2 1 9 2 3 1 7
jet black	74·11	0 4 8 - 2 1 9 2 3 1 8

SNOOT

COLOUR	Ø·H (mm)	ORDER CODE
traffic white	74·25	0 4 8 - 2 1 9 1 1 1 7
jet black	74·25	0 4 8 - 2 1 9 1 1 1 8

SNOOT WITH HONEYCOMB LOUVER

COLOUR	Ø·H (mm)	ORDER CODE
traffic white	74·25	0 4 8 - 2 1 9 1 2 1 7
jet black	74·25	0 4 8 - 2 1 9 1 2 1 8

Daily Paper, Amsterdam

Países Bajos

Arquitecto

Own Space Studio –
Floor Hoeke

Lighting Design

XAL

Fotografía


PRJCT WRKS



Productos utilizados



BO 55 / 70 track



SASSO PRO 100
adjustable flush
round recessed





