



SASSO 60 base 2 lamps

ceiling


EN Cylindrical spotlight made of aluminium; light inset lacquered; housing powder coated; light inset rotatable and tiltable; double lamps; surface mounted housing in aluminium incl. converter; mounting plate with pre-assembled converter unit can be pre-mounted; luminaire housing can be attached without tools by interlock; precise radiation characteristic due to high quality lens system; COB (Chip on Board) technology for maximum efficiency; no multiple shadows; efficient LEDs with very good colour rendering; luminaire for through wiring

ES Proyector cilíndrico de aluminio; inserto lumin. pintado; carcasa con recubr. de polvo; elemento de luz girable e inclinable; con dos luces; carcasa de aluminio para montaje en superficie, incluido convertidor; placa de montaje con convertidor premontado / premontable; cuerpo luminoso insertable por enclavamiento y sin necesidad de herramienta; proyección precisa con óptica de lente de alta calidad; Chip on Board que proporciona una máxima eficiencia; no sombras múltiples; LEDS de eficiencia que proporcionan una alta reproducción cromática; luminaria para cableado pasante

Quickinfo

2700 K, 3000 K, 3500 K, 4000 K
CRI ≥ 90 / 2 SDCM
UGR ≤ 10 , UGR ≤ 13 , UGR ≤ 16 ,
UGR ≤ 19
hasta 93 lm/W
L80 / 50000 h
DALI-2, non attenuable
IP20

Types



Color



Color interno



Distribución luminosa



glare control
(UGR ≤ 16)



easy mounting
no visible
screws



CRI ≥ 95 2
SDCM
(optional)



SASSO 60 base round adjustable 2 lamps ceiling



SPOT CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
20.8 W	2700 K	1470 lm	71 lm/W	0 4 8 - 3 1 4 0 9 S
	3000 K	1520 lm	73 lm/W	0 4 8 - 3 1 4 0 0 S
	3500 K	1550 lm	75 lm/W	0 4 8 - 3 1 4 0 2 S
	4000 K	1600 lm	77 lm/W	0 4 8 - 3 1 4 0 1 S

The data values for the luminous flux may differ for specific order options by -8%. Luminous flux value refers to inner colour traffic white.

MEDIUM CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
20.5 W	2700 K	1750 lm	85 lm/W	0 4 8 - 3 1 4 0 9 M
	3000 K	1810 lm	88 lm/W	0 4 8 - 3 1 4 0 0 M
	3500 K	1850 lm	90 lm/W	0 4 8 - 3 1 4 0 2 M
	4000 K	1890 lm	92 lm/W	0 4 8 - 3 1 4 0 1 M

The data values for the luminous flux may differ for specific order options by -9%. Luminous flux value refers to inner colour traffic white.

FLOOD CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
20.5 W	2700 K	1660 lm	81 lm/W	0 4 8 - 3 1 4 0 9 F
	3000 K	1720 lm	84 lm/W	0 4 8 - 3 1 4 0 0 F
	3500 K	1760 lm	86 lm/W	0 4 8 - 3 1 4 0 2 F
	4000 K	1800 lm	88 lm/W	0 4 8 - 3 1 4 0 1 F

The data values for the luminous flux may differ for specific order options by -15%. Luminous flux value refers to inner colour traffic white.

WIDE FLOOD CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
20.5 W	2700 K	1750 lm	85 lm/W	0 4 8 - 3 1 4 0 9 W
	3000 K	1820 lm	89 lm/W	0 4 8 - 3 1 4 0 0 W
	3500 K	1860 lm	91 lm/W	0 4 8 - 3 1 4 0 2 W
	4000 K	1900 lm	93 lm/W	0 4 8 - 3 1 4 0 1 W

The data values for the luminous flux may differ for specific order options by -11%. Luminous flux value refers to inner colour traffic white.

Order options

CONTROL		COLOUR		INNER COLOUR	
non DIM	1	jet black RAL 9005	1	jet black	1
DALI-2	3	traffic white RAL 9016	7	matt silver	4
				traffic white	7
				gold dust	9

Einfamilienhaus EFF, Austria


Austria

Arquitecto
STUDIO WG3

Fotografía
Heldentheater



Productos utilizados



SASSO 60 base 2
lamps ceiling

