



## MOVE IT 45 system

trimless / surface / suspended


**EN** Extruded aluminium profile with 45mm width groove; for trimless installation in plasterboard ceilings (wall or ceiling mounting) with 12.5mm ceiling thickness; or for wall-/ceiling surface mounting or suspended mounting (cable suspension, height adjustment without tools, incl. black feed); optional with indirect light component for additional accentuation of the ceiling; for lighting systems, 90° angle connectors for flexible system design; node connectors, up to 4 profile connection options; with power track profile for take off of supply voltage and DALI signal; surf. anod. or powder coated; insets can be installed flexibly and without tools by means of magnetic holders + locking; sound absorbing accessories available

**ES** Perfil de alum. extruido con ancho de junta de 45 mm; para encastre sin bordes en planchas de yeso laminado (montaje pared o techo) de 12,5 mm de espesor; o para montaje en pared/techo o suspendido (suspensión por cable, ajuste de altura sin herramienta, cable de alim. negro incluido); componentes de luz indir. opcionales para realce adicional del techo; para sistemas de iluminación, conect. angl. de 90° para la configur. flexible del sistema; conector de nodos, conex. de hasta 4 perfiles; con perfil de carril electrif. para toma de suministro eléct. y señal DALI; superficie anodiz. o recub. de pintura en polvo; montaje flexible y sin herram. de los elem. de luz mediante un soporte magnético con bloqueo; accesorios absorb. del ruido disponibles


### Quickinfo

3000K  
CRI ≥ 90, 2 SDCM  
up to 118lm/W  
L80 @ 50 000h  
non DIM, DALI-2


### Types




### connector



### Colours



custom cut on  
building site



acoustic  
elements

## Order options

### CONTROL

non DIM	1
DALI-2	3

### MATERIAL COLOUR

● jet black RAL 9005







## Options on request

### CONNECTOR

T-connector
X-connector

### INSTALLATION TRACK

acoustic soft ceilings



## MOVE IT 45 trimless



### INSTALLATION TRACK

#### L (mm)

617	channel
1217	channel
2417	channel
3622	channel
cust. cut	channel (non DIM)
cust. cut	channel (DALI-2)
692x648	channel corner* 90°
661x661	channel corner* ceiling to wall 90°

\*incl. electrical connector set

#### ORDER CODE

050-72320	8
050-72340	8
050-72380	8
050-72390	8
E83551	8
E83521	8
050-72310	8
050-72311	8

## Accessories

### END CAPS

#### TYPE

end caps (pair)

#### ORDER CODE

050-72300	8
-----------	---

### BLIND COVER

#### L (mm)

1217
2417
3622
custom cut

#### ORDER CODE

050-70340	8
050-70380	8
050-70390	8
E83500	8B

blind cover can be shortened as desired

### CONNECTOR SET

#### TYPE

linear connector (non DIM, DALI-2)
linear connector flexible
mechanical linear connector (pair)

#### ORDER CODE

050-20311	30
050-20321	0
050-20111	10

### POWER FEEDER UNIT

#### TYPE

non DIM 2×2,5mm <sup>2</sup>
DALI-2 2×2,5 + 2×0,5mm <sup>2</sup>

#### ORDER CODE

050-20201	10
050-20201	30

cable length 500 mm

## Electrical accessories

see following pages

## Order options

## CONTROL

non DIM	1
DALI-2	3

## MATERIAL COLOUR

## INSTALLATION TRACK

● jet black RAL 9005	8
● traffic white 9016 / jet black 9005 P	
● gold dust 260-M / jet black 9005 G	G
● special colours*	X

\*inside always in black

## MATERIAL COLOUR

## NODE CONNECTOR

○ traffic white RAL 9016	7
● jet black RAL 9005	8
● special colours	X

## MATERIAL COLOUR

## NODE LTX / END CAP

● jet black RAL 9005	8
● traffic white 9016 / jet black 9005 P	P
● special colours	X

## MATERIAL COLOUR

## ACCESSORIES

○ traffic white RAL 9016	7
● jet black RAL 9005	8

## NODE CONNECTOR

## MOUNTING TYPE


surface*	1
1500 mm cable susp. chrome	3
1500 mm cable susp. black	4

\*only for L/T/X

## MATERIAL COLOUR

## CABLE SUSPENSION

chrome	0
black	8



## MOVE IT 45 surface / suspended



## INSTALLATION TRACK

L (mm)		ORDER CODE
620	channel	050-73320
1220	channel	050-73340
2420	channel	050-73380
3625	channel	050-73390
cust. cut	channel (non DIM)	E83561
cust. cut	channel (DALI-2)	E83531
653x609	channel corner* 90°	050-73310
666x666	channel corner* ceiling to wall 90°	050-73311

\*incl. electrical connector set

## Accessories

## END CAPS

TYPE	ORDER CODE
end caps (pair)	050-73300

## BLIND COVER

L (mm)	ORDER CODE
1217	050-7034008
2417	050-7038008
3622	050-7039008
custom cut	E83500...8B

blind cover can be shortened as desired

## FLEX NODE CONNECTOR

TYPE	ORDER CODE
FLEX NODE surface mounted	050-20333
FLEX NODE surface mounted incl. feeder	050-202243
FLEX NODE cable suspension 1500 mm	050-20331
FLEX NODE cable susp. 1500 mm incl. feeder	050-20222
NODE end cap* incl. electrical connector	050-733010

\*order for every node connection (channel to node) 1 end cap

## CONNECTOR SET

TYPE	ORDER CODE
mechanical linear conn. incl. 1500 mm cable susp.	050-201131
mechanical linear connector surface	050-2011410
mechanical & electrical linear connector	050-2031230

## POWER FEEDER UNIT

TYPE	L (mm)	ORDER CODE
non DIM 2x2,5 mm <sup>2</sup>	2000	050-2022110
DALI-2 2x2,5 + 2x0,5 mm <sup>2</sup>	2000	050-2022130
non DIM 2x2,5 mm <sup>2</sup>	4000	050-2024110
DALI-2 2x2,5 + 2x0,5 mm <sup>2</sup>	4000	050-2024130

## CEILING FASTENER / CABLE SUSPENSION / CANOPY

TYPE	L (mm)	ORDER CODE
ceiling fastener	67	050-204121
cable suspension*	1500	005-215211
canopy		005-231171

\*use every 1200 mm

## Electrical accessories

see following pages

## Acoustic elements

see following pages

## Order options

## COLOUR TEMPERATURE

3000 K

## CONTROL

non DIM	1
DALI-2	3

## MATERIAL COLOUR

## INSTALLATION TRACK

● jet black RAL 9005	8
● traffic white 9016 / jet black 9005 P	
● gold dust 260-M / jet black 9005 G	
● special colours*	X

\*inside always in black

## MATERIAL COLOUR

## NODE CONNECTOR

○ traffic white RAL 9016	7
● jet black RAL 9005	8
● special colours	X

## MATERIAL COLOUR

## NODE LTX/END CAP

● jet black RAL 9005	8
● traffic white 9016 / jet black 9005 P	
● special colours	X

## MATERIAL COLOUR

## ACCESSORIES

○ traffic white RAL 9016	7
● jet black RAL 9005	8

## NODE CONNECTOR

## MOUNTING TYPE

surface*	1
1500 mm cable susp. chrome	3
1500 mm cable susp. black	4

\*only for L/T/X

## MATERIAL COLOUR

## CABLE SUSPENSION

chrome	0
black	8

## Options on request


## COLOUR RENDERING INDEX

CRI ≥ 98 XPECTRUM

## COLOUR TEMPERATURE

2700 K
4000 K
tunable white 2700–6500 K*

\*DALI-2 DT8



## MOVE IT 45 suspended indirect



## INSTALLATION TRACK INDIRECT

L (mm)	SYSTEM POWER	LUMINOUS FLUX	ORDER CODE
620	6.2 W	648 lm	0 5 0 - 7 4 3 2 5 ▢
1220	15.3 W	1810 lm	0 5 0 - 7 4 3 4 5 ▢
2420	33 W	3890 lm	0 5 0 - 7 4 3 8 5 ▢
3625	51 W	6000 lm	0 5 0 - 7 4 3 9 5 ▢
653x609 corner*	13.1 W	1550 lm	0 5 0 - 7 4 3 1 0 ▢

incl. chrome cable suspension for L=1220/2420/3625 mm

no custom cut on building side; \*incl. electrical connector set

## Accessories

## END CAPS

TYPE	ORDER CODE
end caps (pair)	0 5 0 - 7 3 3 0 0 ▢

## BLIND COVER

L (mm)	ORDER CODE
1217	0 5 0 - 7 0 3 4 0 0 8
2417	0 5 0 - 7 0 3 8 0 0 8
3622	0 5 0 - 7 0 3 9 0 0 8
custom cut	E 8 3 5 0 0 ···· 8 B

blind cover can be shortened as desired

## FLEX NODE CONNECTOR

TYPE	ORDER CODE
FLEX NODE cable suspension 1500 mm	0 5 0 - 2 0 3 3 1 ▢
FLEX NODE cable susp. 1500 mm incl. feeder	0 5 0 - 2 0 2 2 2 ▢
NODE end cap* incl. electrical connector	0 5 0 - 7 3 3 0 1 0 ▢

\*order for every node connection (channel to node) 1 end cap

## CONNECTOR SET

TYPE	ORDER CODE
mechanical linear conn. incl. 1500 mm cable susp.	0 5 0 - 2 0 1 1 3 1 ▢
mechanical & electrical linear connector	0 5 0 - 2 0 3 1 2 3 0


## POWER FEEDER UNIT

TYPE	L (mm)	ORDER CODE
non DIM 2×2,5 mm <sup>2</sup>	2000	0 5 0 - 2 0 2 2 1 1 0
DALI-2 2×2,5 + 2×0,5 mm <sup>2</sup>	2000	0 5 0 - 2 0 2 2 1 3 0
non DIM 2×2,5 mm <sup>2</sup>	4000	0 5 0 - 2 0 2 4 1 1 0
DALI-2 2×2,5 + 2×0,5 mm <sup>2</sup>	4000	0 5 0 - 2 0 2 4 1 3 0

## CABLE SUSPENSION / CANOPY

TYPE	L (mm)	ORDER CODE
cable suspension*	1500	0 0 5 - 2 1 5 2 1 1 ▢
canopy		0 0 5 - 2 3 1 1 7 1 ▢

\*use every 1200 mm



## Electrical accessories

see following pages

## Acoustic elements

see following pages

**LUMINOUS FLUX** value calculated for  
3000 K, CRI ≥ 90, colour white/black


## Order options

## CONTROL

non DIM	1
DALI-2	3

## MATERIAL COLOUR

○ traffic white RAL 9016	7
● jet black RAL 9005	8



## Electrical accessories

## POWER SUPPLY INTRACK supply 220-240 V AC, 48 V, 50-60 Hz


TYPE	EFFICIENCY	MOUNTING	L-W-H (mm)	ORDER CODE
150 W □ PC II η 92 %		intrack	453-43-48	050-2071238
250 W □ PC II η 93 %		intrack	453-43-48	050-2071338

ENEC approved; DALI-2 SELV device integrated

## POWER SUPPLY SURFACE supply 220-240 V AC, 48 V, 50-60 Hz

TYPE	EFFICIENCY	MOUNTING	L-W-H (mm)	ORDER CODE
60 W □ PC II η 88 %		surface	305-144-54	050-20551
100 W □ PC II η 92 %		surface	455-104-40	050-20554
150 W □ PC II η 92 %		surface	455-104-40	050-20552
250 W □ PC II η 93 %		surface	455-104-40	050-20555
320 W ⊕ PC I η 94 %		surface	305-144-54	050-20553


ENEC approved; DALI-2 SELV device integrated



## POWER SUPPLY EXTERNAL supply 220-240 V AC, 48 V, 50-60 Hz

TYPE	EFFICIENCY	MOUNTING	L-W-H (mm)	ORDER CODE
60 W □ PC II η 88 %		external	163-43-32	002-62133
100 W □ PC II η 92 %		external	350-30-18	002-62134
150 W □ PC II η 92 %		external	350-30-18	002-62135
250 W □ PC II η 93 %		external	400-40-22	002-62139
320 W ⊕ PC I η 94 %		external	252-90-44	002-60320

ENEC approved



## DIN RAIL POWER SUPPLY PRO 48 V

220-240 V | 50-60 Hz | ⊕ PC I | MTBF @ 55° ambient temperature  
cascadable max. 5 devices (240 W) or 3 devices (480 W)

TYPE	EFFICIENCY / MTBF	W-H-D (mm)	ORDER CODE
240 W η 92 % / > 400.000 h		60-125-100	005-6220110
480 W η 93 % / > 350.000 h		120-125-100	005-6220210



## DALI-2 SELV DEVICE


TYPE	L-W-H (mm)	ORDER CODE
control unit	213-37-25	050-2061130

necessary to create DALI-2 SELV signal; DALI power supply integrated



## DALI-2 SENSOR

TYPE	L-W-H (mm)	ORDER CODE
ESSENTIAL sensor (brightness & presence)	43-43-48	050-2063378
SENSE sensor (brightness, presence, temperature, sound pressure, humidity, CO <sub>2</sub> )	43-43-48	050-2063278



## WIRELESS TO DALI-2 CONTROL DEVICE

TYPE	L-W-H (mm)	ORDER CODE
Casambi	111-25-45	050-2065230



## WIRELESS TO DALI-2 REPEATER


TYPE	L-W-H (mm)	ORDER CODE
Casambi	111-25-45	050-2066230



DALI-2 SELV device required

## MIDDLE FEED

TYPE	ORDER CODE
DALI-2 2×2,5 + 2×0,5 mm <sup>2</sup> cable length 2000 mm	050-2038130







# LIGHT INSET 45

linear inset 45

## Quickinfo

3000K, 4000K, TW  
CRI ≥ 90, 3 SDCM  
DALI-2

L85 @ 50 000 h  
opal/opal jut-out up to 99lm/W  
microprism. (≤19) up to 77lm/W  
microprism. (≤22) up to 78lm/W

L80 @ 50 000 h  
UGR ≤ 19 / 65° ≤ 1500 cd/m²  
L1 up to 106lm/W  
L2 up to 97lm/W  
L4 up to 104lm/W  
L6 up to 90lm/W

L90 @ 50 000 h  
UGR ≤ 19 / 65° ≤ 1500 cd/m²  
L10 office up to 102lm/W  
L24 office up to 120lm/W

## Types

L1	L2	L4	L6	
				42
48	81	156	231	

L10 office		opal	
	42		42
381		605 1205	


L24 office	
	42
906	

## Colour




## Light distributions

med. flood		rect. med.	wall	wall floor	opal



tunable white  
2700–5000K



CRI ≥ 98  
XPECTRUM

Order options

COLOUR TEMPERATURE	
3000K	5
4000K	6
tunable white 2700–5000 K*	D
*DALI-2 DT8	


CONTROL
DALI-2

MATERIAL COLOUR
● jet black RAL 9005

Options on request

COLOUR RENDERING INDEX
CRI ≥ 98 XPECTRUM

CONTROL
Zigbee 3.0





LIGHT INSET 45




OPAL HIGH PERFORMANCE

INSET POWER	COLOUR TEMP.	LUM. FLUX	L (mm)	ORDER CODE
14.8W	3000K	1100lm	605	0 5 0 - 3 2 1 2 :: 38H
	4000K	1210lm		
29.6W	3000K	2190lm	1205	0 5 0 - 3 2 1 4 :: 38H
	4000K	2420lm		




OPAL JUT-OUT

INSET POWER	COLOUR TEMP.	LUM. FLUX	L (mm)	ORDER CODE
14.8W	3000K	1160lm	605	0 5 0 - 3 2 1 2 :: 38J
	4000K	1270lm		
29.6W	3000K	2310lm	1205	0 5 0 - 3 2 1 4 :: 38J
	4000K	2550lm		



MICROPRISMATIC UGR ≤ 19

INSET POWER	COLOUR TEMP.	LUM. FLUX	L (mm)	ORDER CODE
9.2W	3000K	636lm	605	0 5 0 - 3 2 1 2 :: 38P
	4000K	701lm		
18.3W	3000K	1270lm	1205	0 5 0 - 3 2 1 4 :: 38P
	4000K	400lm		



MICROPRISMATIC UGR ≤ 22

INSET POWER	COLOUR TEMP.	LUM. FLUX	L (mm)	ORDER CODE
23W	3000K	1640lm	605	0 5 0 - 3 2 4 2 :: 38P
	4000K	1750lm		
45W	3000K	3280lm	1205	0 5 0 - 3 2 4 4 :: 38P
	4000K	3500lm		

INSET POWER in watts is the current consumption excluding any ballast  
LUMINOUS FLUX value calculated for CRI ≥ 90, colour black



## Order options

## COLOUR TEMPERATURE

3000 K	5
4000 K	6
tunable white 2700–5000 K*	D

\*DALI-2 DT8

## CONTROL

DALI-2

## LIGHT OPTIC

medium square (UGR ≤ 10)	E
flood square (UGR ≤ 19)	F

## LIGHT OPTIC COLOUR

chrome reflector	0
black reflector*	B

\*not available for spot round, narrow medium round and wallwasher

## MATERIAL COLOUR

● jet black RAL 9005

## Options on request


## LIGHT OPTIC

spot round
narrow medium round
medium round (UGR ≤ 19)
medium square (UGR ≤ 10)
flood round (UGR ≤ 19)
flood square (UGR ≤ 19)
wide flood round
wide flood square
rectangular
wallwasher
wallwasher floor

## LIGHT OPTIC COLOUR

gold reflector

## Planning information




The icons of the light optics are shown in the reflected ceiling plan (RCP) view.


**INSET POWER** in watts is the current consumption excluding any ballast

**LUMINOUS FLUX** value calculated for CRI ≥ 90, colour black, reflector chrome

## L1 LIGHT INSET



## FLOOR



INSET POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
3.4 W	3000 K	up to 338 lm	090-9L1::3▲B■01
	4000 K	up to 361 lm	


choose one light optic ▲ from the options on the left depending on your room needs

## L2 LIGHT INSET



## WALL

2 × wallwasher



INSET POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
6.9 W	3000 K	590 lm	090-9L2::3AB001
	4000 K	633 lm	

## WALL FLOOR

2 × wallwasher floor



INSET POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
6.9 W	3000 K	620 lm	090-9L2::3WB■01
	4000 K	662 lm	


## CORRIDOR

2 × rectangular




INSET POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
6.9 W	3000 K	624 lm	090-9L2::3RB■01
	4000 K	667 lm	

## L4 LIGHT INSET



## FLOOR/CORRIDOR



INSET POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
14 W	3000 K	up to 1350 lm	090-9L4::3▲B■01
	4000 K	up to 1450 lm	

choose one light optic ▲ from the options on the left depending on your room needs

## WALL

4 × wallwasher



INSET POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
14 W	3000 K	1180 lm	090-9L4::3AB001
	4000 K	1270 lm	

## WALL

2 × wallwasher 180° + 2 × wallwasher



INSET POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
14 W	3000 K	1180 lm	090-9L4::3AB002
	4000 K	1270 lm	

## WALL FLOOR

4 × wallwasher floor



INSET POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
14 W	3000 K	1240 lm	090-9L4::3WB■01
	4000 K	1320 lm	

## WALL FLOOR

2 × wallwasher floor 180° + 2 × wallwasher floor



INSET POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
14 W	3000 K	1240 lm	090-9L4::3WB■02
	4000 K	1320 lm	

## Order options

### COLOUR TEMPERATURE

3000 K	5
4000 K	6
tunable white 2700–6500 K*	

\*DALI-2 DT8; L6 light inset 2700–5000 K

### CONTROL

DALI-2	
--------	--

### LIGHT OPTIC COLOUR

chrome reflector	0
black reflector*	B

\*not available for spot round, narrow medium round and medium round and wallwasher

### MATERIAL COLOUR

● jet black RAL 9005	
----------------------	--

## Options on request

### COLOUR RENDERING INDEX

CRI ≥ 98 XPECTRUM\*


\*only for L24 light inset

### LIGHT OPTIC

spot round	
narrow medium round	
medium round (UGR ≤ 19)	
medium square (UGR ≤ 10)	
flood round (UGR ≤ 19)	
flood square (UGR ≤ 19)	
wide flood round	
wide flood square	
rectangular	
wallwasher	
wallwasher floor	

### LIGHT OPTIC COLOUR

gold reflector	
not available for L24 light inset	




## L6 LIGHT INSET



### WALL

6 × wallwasher

INSET POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
21 W	3000 K	1780 lm	090-9 L 6 3 A B 001
15.1 W	4000 K	1900 lm	
	TW 2700–5000 K	1120 lm	090-9 L 6 D 3 A B 001





## L10 LIGHT INSET




### OFFICE UGR ≤ 19

10 × medium square

INSET POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
30 W	3000 K	2840 lm	050-3 2 1 1 3 8 R
22.2 W	4000 K	3060 lm	
	TW 2700–6500 K	2790 lm	050-3 2 1 1 D 3 8 R



## L24 LIGHT INSET



### OFFICE UGR ≤ 19

24 × medium square

INSET POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
21 W	3000 K	2350 lm	050-3 2 1 3 3 8 R
20.2 W	4000 K	2510 lm	
	TW 2700–6500 K	2800 lm	050-3 2 1 3 D 3 8 R

**INSET POWER** in watts is the current consumption excluding any ballast

**LUMINOUS FLUX** value calculated for CRI ≥ 90, colour black, reflector chrome



# JUST 45/55

spotlight inset 45

## Quickinfo


2700 K, 3000 K, 4000 K, CWD, TW  
CRI ≥ 90, 2 SDCM

non DIM, DALI-2

L80 @ 50 000 h  
JUST 45 up to 72lm/W

L90 @ 50 000 h  
JUST 55 up to 88lm/W

## Types



## Colours



## Light distributions


JUST 45



JUST 55



**ARY rod**




**ARY shade**



**TULA**



**PAL**



TW 1800–3000 K  
or 2700–6500 K



CWD  
2000–3000 K

## Order options

## COLOUR TEMPERATURE

2700 K	4
3000 K	5
4000 K	6

colour warm dim. 2000–3000 K\*  
 tunable white 1800–3000 K\*\*  
 tunable white 2700–6500 K\*\*

\*DALI-2 \*\*DALI-2 DT8

## CONTROL

non DIM	1
DALI-2	3

## MATERIAL COLOUR



○ traffic white RAL 9016	7
● jet black RAL 9005	8
special colours	X

## BEAM ANGLE JUST 45

medium 23°	M
flood 44°	F

## BEAM ANGLE JUST 55

spot 16°	S
medium 28°	M
flood 37°	F



## JUST 45



## SPOTLIGHT

INSET POWER	LUMINOUS FLUX	ORDER CODE
6.1 W super spot 8°	297 lm	050-0131333V
11 W	788 lm	050-0131333V
12 W CWD 2000–3000 K	430 lm	050-0131E33
11 W TW 1800–3000 K	555 lm	050-0131L33
11 W TW 2700–6500 K	683 lm	050-0131D33

## JUST 55



## SPOTLIGHT

INSET POWER	LUMINOUS FLUX	ORDER CODE
16.4 W	1430 lm	050-0143333
25.4 W	2010 lm	050-0142333

## Optical accessories

## HONEYCOMB LOUVER

TYPE	Ø-H (mm)	ORDER CODE
JUST 45	42.3	007-1965188
JUST 55	50.3	007-1965598

**INSET POWER** in watts is the current consumption excluding any ballast  
**LUMINOUS FLUX** value calculated for 3000 K, CRI ≥ 90, colour white, lens flood 2700 K -5%, 4000 K +5%

## MOVE IT 45 system

acoustic elements

**EN** Acoustic element made of high quality, self-supporting, recycled PET felt with sound absorbing properties; different versions: choice of square or rectangular design; high quality visual and tactile surface with embossed pattern; foreign fiber inclusions possible; absorption of direct sound and sound reflected from the ceiling; this creates high acoustic performance; for installation in the MOVE IT 45 suspended system composed of node connectors and profiles; subsequent insertion in already installed MOVE IT suspended system possible; installation without tools

**ES** Elemento acústico de fieltro PET reciclado y autoportante de calidad superior con propiedades de absorción del sonido; diferentes variantes: forma opcionalmente cuadrada o rectangular; superficie de alta calidad táctil y visual con motivos en relieve; posible inclusión de partículas extrañas; absorción del sonido directo y del reflejado por el techo; con ello gran rendimiento acústico; para la integración en el sistema suspendido MOVE IT 45, compuesto de uniones y perfiles; posible integración posterior en un MOVE IT suspended system ya instalado; instalación sin herramientas


### Quickinfo

PET felt

♻️ from recycled material

🔥 available as B-s1, d0


### Types



### Colours



easy  
mounting



sound absorption  
by recycled PET



Order options


MATERIAL COLOUR		
<input type="radio"/> white		W
<input type="radio"/> marble grey		D
<input type="radio"/> black		L

Options on request

MATERIAL COLOUR
painted in custom colour

DIMENSIONS
cut in custom dimensions



MOVE IT 45 acoustic suspended



ACOUSTIC ELEMENT

TYPE	L-W-H (mm)	ORDER CODE
square grid inlay	1235·1235·25	0 5 0 - 2 3 1 1 2 1 <input checked="" type="checkbox"/>
half grid inlay	635·1235·25	0 5 0 - 2 3 1 2 2 1 <input checked="" type="checkbox"/>
double grid inlay	2435·1235·25	0 5 0 - 2 3 1 3 2 1 <input checked="" type="checkbox"/>

mounting only in MOVE IT 45 system with NODE connector + track 1220 mm, 620 mm or 2420 mm

ACOUSTIC EXAMPLES

