

MOVE IN flex round

recessed


EN Round spotlight element in aluminium, available in 2 sizes; powder coated; installation without tools in mounting set (trimless or with trim) with ball catch system; special mounting tool for easy installation of the trimless housing available as an accessory; spotlight element height adjustable without tools: flush with the ceiling, or extended 25 mm or 35 mm; spotlight head rotates 360° and tilts 90°; COB (Chip on Board) technology for maximum efficiency; no multiple shadows; energy-efficient LEDs with very good colour rendering; high-quality, aluminium, vapour deposition coated reflector with faceted design; precise radiation characteristic; good glare reduction due to recessed light point plane; optical attachments as accessories

ES Proyector de aluminio redondo en 2 tamaños; recubierto de polvo; instalación sin herramientas mediante kit de montaje (con o sin marco) con sistema inserción de bola; herramienta de montaje especial para la sencilla instalación de la carcasa sin bordes disponible como accesorio; proyector altura ajustable sin herramienta: enrasado al techo, sobresaliente 25 mm o 35 mm; cabezal de proyector giratorio de 360° y orientable 90°; Chip on Board que proporciona una máxima eficiencia; sin formación de sombras; LEDS de alta eficiencia que proporcionan una alta reproducción cromática; reflector de alta calidad vaporizado de aluminio con revestimiento de facetas esféricas; característica proyección precisa; buen control del deslumbramiento mediante plano de punto de luz retranqueado; los accesorios ópticos como accesorios

Quickinfo

2700 K, 3000 K
CRI $\geq$ 90 / 2 SDCM, 3 SDCM
hasta 106 lm/W
L80 / 50000 h, L85 / 50000 h
DALI-2, non attenuable
front IP20

Types



Color



Set de montaje



Distribución luminosa



trimless
installation in
plasterboard



tool-free height
adjustment,
rotatable &
tiltable



MOVE IN 32 flex round



SPOT CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	FIXTURE	ORDER CODE
8.7 W, 250 mA	2700 K	788 lm	91 lm/W	0 6 3 - 8 2 1 1 4 1 ☒ S
	3000 K	817 lm	94 lm/W	0 6 3 - 8 2 1 1 5 1 ☒ S

incl. connection cable 600 mm

MEDIUM CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	FIXTURE	ORDER CODE
8.7 W, 250 mA	2700 K	821 lm	94 lm/W	0 6 3 - 8 2 1 1 4 1 ☒ M
	3000 K	852 lm	98 lm/W	0 6 3 - 8 2 1 1 5 1 ☒ M

incl. connection cable 600 mm

FLOOD CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	FIXTURE	ORDER CODE
8.7 W, 250 mA	2700 K	783 lm	90 lm/W	0 6 3 - 8 2 1 1 4 1 ☒ F
	3000 K	813 lm	93 lm/W	0 6 3 - 8 2 1 1 5 1 ☒ F

incl. connection cable 600 mm



MOVE IN 45 flex round



SUPER SPOT CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	FIXTURE	ORDER CODE
6.9 W, 600 mA	2700 K	406 lm	59 lm/W	0 6 3 - 8 2 2 1 4 1 ☒ V
	3000 K	346 lm	50 lm/W	0 6 3 - 8 2 2 1 5 1 ☒ V

incl. connection cable 600 mm

SPOT CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	FIXTURE	ORDER CODE
12.6 W, 350 mA	2700 K	1110 lm	88 lm/W	0 6 3 - 8 2 2 1 4 1 6 S
12.7 W, 350 mA	2700 K	1120 lm	89 lm/W	0 6 3 - 8 2 2 1 4 1 ☒ S
	3000 K	1160 lm	92 lm/W	0 6 3 - 8 2 2 1 5 1 ☒ S

incl. connection cable 600 mm

MEDIUM CRI ≥ 90

FIXTURE	COLOUR TEMP.	LUM. FLUX	FIXTURE	ORDER CODE
13.2 W, 400 mA	3000 K	1340 lm	102 lm/W	0 6 3 - 8 2 2 1 5 1 6 M
13.4 W, 400 mA	2700 K	1330 lm	100 lm/W	0 6 3 - 8 2 2 1 4 1 ☒ M
	3000 K	1380 lm	104 lm/W	0 6 3 - 8 2 2 1 5 1 ☒ M

incl. connection cable 600 mm

FLOOD CRI ≥ 90


FIXTURE	COLOUR TEMP.	LUM. FLUX	FIXTURE	ORDER CODE
13.2 W, 400 mA	3000 K	1380 lm	104 lm/W	0 6 3 - 8 2 2 1 5 1 6 F
13.4 W, 400 mA	2700 K	1360 lm	102 lm/W	0 6 3 - 8 2 2 1 4 1 ☒ F
	3000 K	1420 lm	106 lm/W	0 6 3 - 8 2 2 1 5 1 ☒ F

incl. connection cable 600 mm

Order options


COLOUR	☒	COLOUR	☒
chrome	4	chrome	4
brushed aluminium	6	traffic white RAL 9016	7
traffic white RAL 9016	7	jet black RAL 9005	8
jet black RAL 9005	8		

Mounting accessories (required)




MOUNTING HOUSING trimless

TYPE	COLOUR	CEILING THICKNESS	Ø-H (mm)	ORDER CODE
for installation in plasterboard ceilings for MOVE IN 32 round	traffic white	9-25 mm	63-93	0 6 3 - 8 8 1 1 1 7



MOUNTING HOUSING trimless


TYPE	COLOUR	CEILING THICKNESS	Ø-H (mm)	ORDER CODE
for installation in plasterboard ceilings for MOVE IN 45 round	traffic white	9-25 mm	75-106	0 6 3 - 8 8 1 2 1 7



MOUNTING HOUSING with trim for installation in ceilings, 2-25 mm

COLOUR	Ø-H (mm)	ORDER CODE
traffic white	65-93	0 6 3 - 8 8 2 1 1 7
jet black	65-93	0 6 3 - 8 8 2 1 1 8

for MOVE IN 32 round



MOUNTING HOUSING with trim for installation in ceilings, 2-25 mm

COLOUR	Ø-H (mm)	ORDER CODE
traffic white	77-107	0 6 3 - 8 8 2 2 1 7
jet black	77-107	0 6 3 - 8 8 2 2 1 8

for MOVE IN 45 round

Mounting accessories (optional)



SPECIAL MOUNTING TOOL

TYPE	Ø-H (mm)	ORDER CODE
for MOVE IN 32 round SPIO 20 necessary to install mounting housing trimless	83-107	0 6 3 - 8 9 1 1 1 0



SPECIAL MOUNTING TOOL


TYPE	Ø-H (mm)	ORDER CODE
for ARY MOVE IN 45 NOBA TULA necessary to install mounting housing trimless	100-107	0 6 3 - 8 9 1 2 1 0

Electrical accessories (required)


POWER SUPPLY 198-264 V AC

TYPE	EFFICIENCY	L-W-H (mm)	ORDER CODE
350 mA 40 W DALI-2 PC2	η 89 %	197-29-21	0 0 2 - 9 0 7 2 0
350 mA 22 W non DIM PC2	η 89 %	180-30-21	0 0 2 - 9 0 7 2 2
400 mA 22 W non DIM PC2	η 89 %	180-30-21	0 0 2 - 9 0 7 2 4
600 mA 30 W non DIM PC1	η 89 %	180-30-21	0 0 2 - 9 0 7 2 6
400 mA 40 W DALI-2 PC2	η 89 %	197-29-21	0 0 2 - 9 0 7 2 8
600 mA 40 W DALI-2 PC2	η 89 %	197-29-21	0 0 2 - 9 0 7 2 9
250 mA 10 W non DIM PC2	η 80 %	65-39-20	0 0 2 - 9 0 7 4 2
250 mA 10 W DALI-2 PC2	η 82 %	147-33-23	0 0 2 - 9 0 7 4 3

Electrical accessories (optional)



DIN RAIL LED DRIVER		
TYPE	L·W·H (mm)	ORDER CODE
DALI-2 DT6 1-2 addresses	36·88·59	0 0 5 - 6 1 2 1 0 3 0
200 -1050 mA settable const. current 2×42W 48V DC U OUT 10–40V		



DIN RAIL POWER SUPPLY		
L·W·H (mm)		ORDER CODE
72·90·63		0 0 5 - 6 5 2 0 2 1 0
220-240 V AC 160W 48V DC constant voltage		

Optical accessories (optional)

HONEYCOMB LOUVER jet black

TYPE	Ø·H (mm)	ORDER CODE
for BO 32 JUST 32 MOVE IN 32 TARO 32 TILA 32	30·3	0 0 7 - 1 9 6 5 1 6 8
for BO 45 JUST 45 MOVE IN 45 TARO 45 TULA micro	42·3	0 0 7 - 1 9 6 5 1 8 8

OVAL LENS

TYPE	Ø·H (mm)	ORDER CODE
for BO 32 MOVE IN 32	30·3	0 0 7 - 1 9 6 5 8 6 0
for BO 45 MOVE IN 45 TULA micro	42·3	0 0 7 - 1 9 6 5 8 8 0

SOFT LENS

TYPE	Ø·H (mm)	ORDER CODE
for BO 32 MOVE IN 32	30·3	0 0 7 - 1 9 6 5 9 6 0
for ARY BO 45 MOVE IN 45 TULA micro	42·3	0 0 7 - 1 9 6 5 9 8 0

WALLWASHER LENS

TYPE	Ø·H (mm)	ORDER CODE
for BO 32 MOVE IN 32	30·3	0 0 7 - 1 9 6 5 7 6 0
for ARY BO 45 MOVE IN 45 TULA micro	42·3	0 0 7 - 1 9 6 5 7 8 0