



## MOVE IN flex

recessed


**EN** Round spotlight element in aluminium, available in 2 sizes; powder coated; installation without tools in mounting set (trimless or with trim) with ball catch system; special mounting tool for easy installation of the trimless housing available as an accessory; spotlight element height adjustable without tools: flush with the ceiling, or extended 25 mm or 35 mm; spotlight head rotates 360° and tilts 90°; COB (Chip on Board) technology for maximum efficiency; no multiple shadows; energy-efficient LEDs with very good colour rendering; high-quality, aluminium, vapour deposition coated reflector with faceted design; precise radiation characteristic; good glare reduction due to recessed light point plane; optical attachments as accessories

**ES** Proyector de aluminio redondo en 2 tamaños; recubierto de polvo; instalación sin herramientas mediante kit de montaje (con o sin marco) con sistema inserción de bola; herramienta de montaje especial para la sencilla instalación de la carcasa sin bordes disponible como accesorio; proyector altura ajustable sin herramienta: enrasado al techo, sobresaliente 25 mm o 35 mm; cabezal de proyector giratorio de 360° y orientable 90°; Chip on Board que proporciona una máxima eficiencia; sin formación de sombras; LEDS de alta eficiencia que proporcionan una alta reproducción cromática; reflector de alta calidad vaporizado de aluminio con revestimiento de facetas esféricas; característica proyección precisa; buen control del deslumbramiento mediante plano de punto de luz retransmitido; los accesorios ópticos como accesorios

### Quickinfo

2700 K, 3000 K  
CRI ≥ 90, 2 SDCM  
MOVE IN 32 up to 86 lm/W  
MOVE IN 45 up to 95 lm/W  
L80 @ 50 000 h  
non DIM, DALI-2

### Types




### Inset colours



### Housing colours



### Light distributions



tool-free height  
adjustment,  
rotatable & tiltable



trimless  
installation in  
plasterboard

## Order options

COLOUR TEMPERATURE	
2700 K	4
3000 K	5

INSET COLOUR	
○ traffic white RAL 9016	7
● jet black RAL 9005	8
● brushed aluminium	6
● chrome	4

HOUSING COLOUR	
○ traffic white RAL 9016	7
● jet black RAL 9005	8

BEAM ANGLE	
MOVE IN 32/45	
super spot 8°*	V
spot 18°/14°	S
medium 23°/24°	M
flood 37°/39°	F







\*only for MOVE IN 45

## Options on request

INSET COLOUR	
● gun metal	
● brushed brass	

HOUSING COLOUR	
special colours	

POWER SUPPLY	
DIM 1–10V	



## MOVE IN 32 flex



SPOTLIGHT incl. connection cable 600 mm

INSET POWER	LUMINOUS FLUX	ORDER CODE
8.8 W 36 Vf 250 mA	755 lm	0 6 3 - 8 2 1 1 : 1 1 4

## MOVE IN 45 flex



SPOTLIGHT incl. connection cable 600 mm

INSET POWER	LUMINOUS FLUX	ORDER CODE
12.8 W 37 Vf 350 mA	spot 1010 lm	0 6 3 - 8 2 2 1 : 1 1 4 S
13.5 W 36 Vf 400 mA	1280 lm	0 6 3 - 8 2 2 1 : 1 1 4
6.9 W 11 Vf 600 mA	super spot 356 lm	0 6 3 - 8 2 2 1 : 1 1 4 V

## Mounting accessories

## MOUNTING HOUSING TRIMLESS

for installation in plasterboard ceilings 9–25 mm

TYPE	Ø-H (mm)	ORDER CODE
MOVE IN 32	63-93	0 6 3 - 8 8 1 1 1 1 7
MOVE IN 45	75-106	0 6 3 - 8 8 1 2 1 1 7

## MOUNTING HOUSING WITH TRIM

for installation in ceilings from 2–25 mm

TYPE	Ø-H (mm)	ORDER CODE
MOVE IN 32	65-93	0 6 3 - 8 8 2 1 1 1 1
MOVE IN 45	77-107	0 6 3 - 8 8 2 2 1 1 1

## SPECIAL MOUNTING TOOL

TYPE	Ø-H (mm)	ORDER CODE
MOVE IN 32	83-9	0 6 3 - 8 9 1 1 1 1 0
MOVE IN 45	100-9	0 6 3 - 8 9 1 2 1 1 0

necessary to install mounting housing trimless

## Electrical accessories

## POWER SUPPLY 220–240 V AC, 50–60 Hz, □ PC II

TYPE	EFFICIENCY	L-W-H (mm)	ORDER CODE
250 mA   non DIM	η 80 %	65-39-20	0 0 2 - 9 0 7 4 2
250 mA   DALI-2	η 82 %	147-33-23	0 0 2 - 9 0 7 4 3
350 mA   non DIM	η 85 %	180-30-21	0 0 2 - 9 0 7 2 2
350 mA   DALI-2	η 83 %	210-30-21	0 0 2 - 9 0 7 2 3
400 mA   non DIM	η 88 %	180-30-21	0 0 2 - 9 0 7 2 4
400 mA   DALI-2	η 84 %	210-30-21	0 0 2 - 9 0 7 2 5
600 mA   non DIM	η 87 %	180-30-21	0 0 2 - 9 0 7 2 6
600 mA   DALI-2	η 85 %	210-30-21	0 0 2 - 9 0 7 2 7

MOVE IN 32 trimless revision opening required; \*insert before mounting set with trim

## DIN RAIL COMPONENTS

TYPE	W-H-D (mm)	ORDER CODE
POWER SUPPLY 220-240 V AC	72-90-63	0 0 5 - 6 5 2 0 2 1 0
160 W   48 V DC constant voltage		
LED DRIVER DALI-2 DT6 1–2 addr.	36-88-59	0 0 5 - 6 1 2 1 0 3 0
200–1050 mA settable const. current		
2 × 42 W   48 V DC   U <sub>OUT</sub> 10–40 V		

for more details and components see page Seite 981

## Optical accessories

## HONEYCOMB LOUVER

TYPE	Ø-H (mm)	ORDER CODE
MOVE IN flex 32	30-3	0 0 7 - 1 9 6 5 1 6 8
MOVE IN flex 45	42-3	0 0 7 - 1 9 6 5 1 8 8

INSET POWER is the current

consumption excluding any ballast

LUMINOUS FLUX value calculated for

3000 K, CRI ≥ 90, colour white, reflector flood

2700 K -6 %