




UNICO wall

surface


EN Rectangular wall surface mounted multi-uplight made of aluminium; equipped with one light inset (1 LAMP) / two (2 LAMPS) / four (4 LAMPS) light insets; luminaire housing can be attached to mounting plate without tools by interlock; converter integrated into luminaire housing; surface powder coated; high-quality reflector with micro-faceted, aluminum-vaporised surface; homogeneous wall or ceiling illumination through uniform light distribution; energy-efficient high power LEDs with very good colour rendering; luminaire for through wiring

ES Uplight múltiple rectang. alum. para montaje superf.; equipado con un inserto luminoso (1 LAMP) / dos (2 LAMPS) / cuatro (4 LAMPS) insertos lumin.; cuerpo luminoso insertable en la placa de montaje por enclavamiento y sin necesidad de herramienta; convertidor integrado en el cuerpo luminoso; superficie con recubrimiento de pintura en polvo; reflector de alta calidad con superficie de múltiples facetas revestida con aluminio por vaporización; iluminación homogénea de la pared o bien del techo mediante distribución uniforme de la luz; LEDS de alta eficiencia que proporcionan una alta reproducción cromática; luminaria para cableado pasante

Quickinfo

2700 K, 3000 K, 4000 K
CRI $\geq$ 90 / 3 SDCM
hasta 47 lm/W
L80 / 50000 h, L90 / 50000 h
DALI-2, non attenuable
IP20

Types



Color



Distribución luminosa



homogeneous
ceiling
illumination



safety glass for
dust protection



tunable white
2700 – 5000 K
(optional)



UNICO wall 1 lamp surface




WIDE FLOOR CRI ≥ 90, non DIM

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
5.8 W	2700 K	220 lm	38 lm/W	0 9 0 - 0 L 1 4 1 T ☒ 0 0 1
	3000 K	235 lm	41 lm/W	0 9 0 - 0 L 1 5 1 T ☒ 0 0 1
	4000 K	244 lm	42 lm/W	0 9 0 - 0 L 1 6 1 T ☒ 0 0 1




UNICO wall 2 lamps surface




WIDE FLOOR CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
17.3 W	2700 K	650 lm	38 lm/W	0 9 0 - 0 L 2 4 ☒ T ☒ 0 0 1
	3000 K	693 lm	40 lm/W	0 9 0 - 0 L 2 5 ☒ T ☒ 0 0 1
	4000 K	744 lm	43 lm/W	0 9 0 - 0 L 2 6 ☒ T ☒ 0 0 1




UNICO wall 4 lamps surface



WIDE FLOOR CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
29.8 W	2700 K	1230 lm	41 lm/W	0 9 0 - 0 L 4 4 ☒ T ☒ 0 0 1
	3000 K	1310 lm	44 lm/W	0 9 0 - 0 L 4 5 ☒ T ☒ 0 0 1
	4000 K	1410 lm	47 lm/W	0 9 0 - 0 L 4 6 ☒ T ☒ 0 0 1



Order options

CONTROL

non DIM

DALI-2



1

3

COLOUR

jet black RAL 9005

white aluminium RAL 9006

traffic white RAL 9016



B

G

W