

SASSO 100 round downlight

trim

048-2700617X 048-2796317 002-90776



Proyecto / Tipo
Notas
Cantidad / Fecha



↑ IP20 ↓ IP44	220-240V	X-PERT	X-PERT
------------------	----------	--------	--------

General

Techo , Empotrado
blanco , RAL9016 ¹
Set de montaje blanco tráfico
delante IP44 , detrás IP20
2170 lm

LED

4000 K
CRI ≥ 90
L80 / 50000 h
MacAdam inicial ≤ 2 SDCM
R _g : 97 , R _r : 90 , R _{t(1-15)} : 89
MR 0.81
MDER 0.74

Óptico

super wide flood
ángulo de haz 69°
PstLM ≤ 1.0 ²
SVM ≤ 0.4 ²

Eléctrico

DALI-2
29.2 W
inserto 24.8 W
36 Vf
700 mA
CP2 220-240V
74 lm/W
1 DALI Addr.

Físico

borde
diámetro 118 mm
altura 75 mm
0.48 kg


Orificio

diámetro 108 mm
espesor mín. del techo 2 mm
espesor máx. del techo 25 mm
profundidad empotrada 80 mm

¹ Código RAL

² Valor del producto continente a plena carga (no atenuado)

Distribución luminosa



Diseño del producto



Instrucciones de montaje



Calculadora de iluminación

