

# SASSO 60 square downlight

trim 2 lamps

048-2612414W 048-269931G 002-90771



Proyecto / Tipo
Notas
Cantidad / Fecha



↑ IP20 ↓ IP44	220-240V	X-PERT	X-PERT
------------------	----------	--------	--------

## General

Techo , Empotrado
plata mate
Set de montaje plateado-gris
delante IP44 , detrás IP20
2040 lm

## LED

2700 K
CRI ≥ 90
L80 / 50000 h
MacAdam inicial ≤ 2 SDCM
R <sub>g</sub> : 99 , R <sub>r</sub> : 91 , R <sub>t(1-15)</sub> : 89
MR 0.53
MDER 0.48

## Óptico

wide flood
ángulo de haz 52°
≥65° <1500 cd/m <sup>2</sup>
PstLM ≤ 1.0 <sup>1</sup>
SVM ≤ 0.4 <sup>1</sup>

## Eléctrico

non atenuable
25.2 W
total de insertos 21.4 W
CP2 220-240V
81 lm/W

## Físico


borde
longitud 147 mm
ancho 81 mm
altura 48 mm
0.28 kg

## Orificio


longitud 138 mm
ancho 73 mm
espesor mín. del techo 2 mm
espesor máx. del techo 25 mm
profundidad empotrada 90 mm

<sup>1</sup> Valor del producto continente a plena carga (no atenuado)

## Distribución luminosa



## Diseño del producto



## Instrucciones de montaje



## Calculadora de iluminación

