

SASSO 60 square downlight

trim

048-2612412W 048-269731G 002-90771



Proyecto / Tipo	
Notas	
Cantidad / Fecha	



↑ IP20 ↓ IP44	220-240V	X-PERT	X-PERT
------------------	----------	--------	--------

General

Techo , Empotrado
cromo
Set de montaje plateado-gris
delante IP44 , detrás IP20
1030 lm

LED

2700 K
CRI ≥ 90
L80 / 50000 h
MacAdam inicial ≤ 2 SDCM
R _g : 99 , R _f : 91 , R _{f(1-15)} : 89
MR 0.53
MDER 0.48

Óptico

wide flood
ángulo de haz 52°
≥65° <1500 cd/m ²
PstLM ≤ 1.0 ¹
SVM ≤ 0.4 ¹

Eléctrico

non atenuable
12.6 W
CP2 220-240V
82 lm/W

Físico


borde
longitud 80 mm
ancho 80 mm
altura 48 mm

Orificio


longitud 73 mm
ancho 73 mm
espesor mín. del techo 2 mm
espesor máx. del techo 25 mm
profundidad empotrada 60 mm

¹ Valor del producto continente a plena carga (no atenuado)

Distribución luminosa



Diseño del producto



Instrucciones de montaje



Calculadora de iluminación

