

SASSO 60 round downlight

trim 2 lamps

048-2602619W 048-2698318 002-90762



Proyecto / Tipo
Notas
Cantidad / Fecha



↑ IP20 ↓ IP44	220-240V	360°	X-PERT	X-PERT
------------------	----------	------	--------	--------

General

Techo , Empotrado
rotación 360°
dorado , RAL260-M ¹
Set de montaje negro intenso
delante IP44 , detrás IP20
2200 lm

LED

4000 K
CRI ≥ 90
L80 / 50000 h
MacAdam inicial ≤ 2 SDCM
R _g : 97 , R _f : 90 , R ₍₁₋₅₎ : 89
MR 0.81
MDER 0.74

Óptico

wide flood
ángulo de haz 55°
≥65° <1500 cd/m²
PstLM ≤ 1.0 ²
SVM ≤ 0.4 ²

Eléctrico

DALI-2
25.2 W
total de insertos 21.4 W
CP2 220-240V
87 lm/W
1 DALI Addr.

Físico


borde
longitud 147 mm
ancho 80 mm
altura 48 mm
0.34 kg

Orificio


diámetro 70 mm
longitud 136 mm
espesor mín. del techo 2 mm
espesor máx. del techo 25 mm
profundidad empotrada 110 mm

¹ Código RAL
² Valor del producto continente a plena carga (no atenuado)

Distribución luminosa



Diseño del producto



Instrucciones de montaje



Calculadora de iluminación

