

SASSO 60 round downlight

trim

048-2602612F 048-2696317 002-90771



Proyecto / Tipo	
Notas	
Cantidad / Fecha	



↑ IP20 ↓ IP44	220-240V	↻	X-PERT	X-PERT
------------------	----------	---	--------	--------

General

Techo , Empotrado
rotación 360°
chromo
Set de montaje blanco tráfico
delante IP44 , detrás IP20
1140 lm

LED

4000 K
CRI ≥ 90
L80 / 50000 h
MacAdam inicial ≤ 2 SDCM
R _g : 97 , R _f : 90 , R ₍₁₋₁₅₎ : 89
MR 0.81
MDER 0.74

Óptico

flood
ángulo de haz 46°
UGR < 19 , ≥ 65° < 1500 cd/m²
PstLM ≤ 1.0 ¹
SVM ≤ 0.4 ¹

Eléctrico

non atenuable
12.6 W
CP2 220-240V
90 lm/W

Físico


borde
diámetro 80 mm
altura 48 mm

Orificio

diámetro 73 mm
espesor mín. del techo 2 mm
espesor máx. del techo 25 mm
profundidad empotrada 60 mm

¹ Valor del producto continente a plena carga (no atenuado)

Distribución luminosa



Diseño del producto



Instrucciones de montaje



Calculadora de iluminación

