

SASSO 60 round downlight

trim

048-2602512F 048-269631G 002-90762



Proyecto / Tipo
Notas
Cantidad / Fecha



↑ IP20 ↓ IP44	220-240V	↻	X-PERT	X-PERT
------------------	----------	---	--------	--------

General

Techo , Empotrado
rotación 360°
chromo
Set de montaje plateado-gris
delante IP44 , detrás IP20
1070 lm

LED

3000 K
CRI ≥ 90
L80 / 50000 h
MacAdam inicial ≤ 2 SDCM
R _g : 100 , R _f : 91 , R _{f1-15} : 88
MR 0.59
MDER 0.53

Óptico

flood
ángulo de haz 46°
UGR < 19 , ≥ 65° < 1500 cd/m²
PstLM ≤ 1.0 ¹
SVM ≤ 0.4 ¹

Eléctrico

DALI-2
12.6 W
CP2 220-240V
85 lm/W
1 DALI Addr.

Físico


borde
diámetro 80 mm
altura 48 mm

Orificio

diámetro 73 mm
espesor mín. del techo 2 mm
espesor máx. del techo 25 mm
profundidad empotrada 110 mm

¹ Valor del producto continente a plena carga (no atenuado)

Distribución luminosa



Diseño del producto

