

# SASSO 60 round downlight

trim

048-2602411W 048-2696318 002-90762



Proyecto / Tipo
Notas
Cantidad / Fecha



↑ IP20 ↓ IP44	220-240V	360°	X-PERT	X-PERT
------------------	----------	------	--------	--------

## General

Techo , Empotrado
rotación 360°
negro , RAL9005 <sup>1</sup>
Set de montaje negro intenso
delante IP44 , detrás IP20
945 lm

## LED

2700 K
CRI ≥ 90
L80 / 50000 h
MacAdam inicial ≤ 2 SDCM
R <sub>g</sub> : 99 , R <sub>f</sub> : 91 , R <sub>(1-15)</sub> : 89
MR 0.53
MDER 0.48

## Óptico

wide flood
ángulo de haz 55°
≥65° <1500 cd/m <sup>2</sup>
PstLM ≤ 1.0 <sup>2</sup>
SVM ≤ 0.4 <sup>2</sup>

## Eléctrico

DALI-2
12.6 W
CP2 220-240V
75 lm/W
1 DALI Addr.

## Físico


borde
diámetro 80 mm
altura 48 mm
0.27 kg

## Orificio

diámetro 73 mm
espesor mín. del techo 2 mm
espesor máx. del techo 25 mm
profundidad empotrada 110 mm

<sup>1</sup> Código RAL  
<sup>2</sup> Valor del producto continente a plena carga (no atenuado)

## Distribución luminosa



## Diseño del producto

