



MITA circle 450

suspended


^{EN} Ring shaped luminaire housing in die-cast aluminium; extremely slim design; surface powder coated; suspended; with height adjustable rod suspension (chrome), feed in rod; electronic operating unit installed in the canopy; optional: blind cover to cover the cut-out, held by magnet, available as an accessory; high gloss reflector with faceted design; HPO (High Performance Opal) cover for uniform illumination; either with direct or direct / indirect light distribution; energy-efficient LEDs with very good colour rendering

^{ES} Cuerpo con forma de anillo y fabricado en aluminio; forma extremadamente esbelta; superficie con recubrimiento de pintura en polvo; suspendido; con suspensión acortable de tubo pendular (cromo), línea de alimentación en tubo pendular; driver instalado en el baldaquino; opcional: cubierta opaca de fijación a recorte de techo con imán disponible como accesorio adicional; reflector de alto brillo con óptica facetada; difusor opal de alta calidad que proporciona una iluminación uniforme; opcionalmente con característica de emisión directa o directa/indirecta; LEDS de alta eficiencia que proporcionan una alta reproducción cromática

Quickinfo

3000 K, 4000 K
 CRI ≥ 80 , CRI ≥ 90 / 3 SDCM
 UGR ≤ 13 , UGR ≤ 16 , UGR ≤ 19
 hasta : 4,750 lm / $\uparrow$ 4,380 lm
 hasta 160 lm/W
 L90 / 50000 h
 DALI-2
 Opal, Reflector
 IP20

Types



Color



Reflector



Distribución luminosa



dark chrome
reflector option



up to 139 lm/W
(high efficiency)




version with
opal cover




magnetic blind
cover



DIN EN 12464-1
UGR ≤ 19



MITA circle 450 suspended



DIRECT | REFLECTOR (UGR ≤ 19) DALI-2

SYSTEM	COLOUR TEMP.	REFLECTOR	CRI ≥	LUM. FLUX	SYSTEM	ORDER CODE
30.0 W	3000 K	chrome	80	4210 lm	140 lm/W	0 7 4 - 7 6 1 1 5 3 ☒ R
			90	3630 lm	121 lm/W	0 7 4 - 7 6 1 1 0 3 ☒ R
		dark chr.	80	3010 lm	100 lm/W	0 7 4 - 7 6 1 1 5 3 ☒ B
			90	2600 lm	87 lm/W	0 7 4 - 7 6 1 1 0 3 ☒ B
	4000 K	chrome	80	4790 lm	160 lm/W	0 7 4 - 7 6 1 1 6 3 ☒ R
			90	3920 lm	131 lm/W	0 7 4 - 7 6 1 1 1 3 ☒ R
		dark chr.	80	3430 lm	114 lm/W	0 7 4 - 7 6 1 1 6 3 ☒ B
			90	2800 lm	93 lm/W	0 7 4 - 7 6 1 1 1 3 ☒ B
	40.0 W	chrome	80	5470 lm	137 lm/W	0 7 4 - 7 6 2 1 5 3 ☒ R
			90	4720 lm	118 lm/W	0 7 4 - 7 6 2 1 0 3 ☒ R
		dark chr.	80	3920 lm	98 lm/W	0 7 4 - 7 6 2 1 5 3 ☒ B
			90	3380 lm	85 lm/W	0 7 4 - 7 6 2 1 0 3 ☒ B
	4000 K	chrome	80	6230 lm	156 lm/W	0 7 4 - 7 6 2 1 6 3 ☒ R
			90	5100 lm	128 lm/W	0 7 4 - 7 6 2 1 1 3 ☒ R
		dark chr.	80	4460 lm	112 lm/W	0 7 4 - 7 6 2 1 6 3 ☒ B
			90	3650 lm	91 lm/W	0 7 4 - 7 6 2 1 1 3 ☒ B

OPAL | DIRECT DALI-2

SYSTEM	COLOUR TEMP.	CRI ≥	LUM. FLUX	SYSTEM	ORDER CODE
24.9 W	3000 K	80	2760 lm	111 lm/W	0 7 4 - 7 6 1 1 5 3 ☒ O
		90	2380 lm	96 lm/W	0 7 4 - 7 6 1 1 0 3 ☒ O
	4000 K	80	3140 lm	126 lm/W	0 7 4 - 7 6 1 1 6 3 ☒ O
		90	2570 lm	103 lm/W	0 7 4 - 7 6 1 1 1 3 ☒ O

DIRECT / INDIRECT POWER | REFLECTOR (UGR ≤ 19) DALI-2


SYSTEM	COLOUR TEMP.	REFLECTOR	CRI ≥	LUM. FLUX	SYSTEM	ORDER CODE
60.0 W	3000 K	chrome	80	↓4170/↑3850 lm	134 lm/W	0 7 4 - 7 6 5 1 5 3 ☒ R
			90	↓3590/↑3320 lm	115 lm/W	0 7 4 - 7 6 5 1 0 3 ☒ R
		dark chr.	80	↓2970/↑3850 lm	114 lm/W	0 7 4 - 7 6 5 1 5 3 ☒ B
			90	↓2560/↑3320 lm	98 lm/W	0 7 4 - 7 6 5 1 0 3 ☒ B
	4000 K	chrome	80	↓4750/↑4380 lm	152 lm/W	0 7 4 - 7 6 5 1 6 3 ☒ R
			90	↓3880/↑3580 lm	124 lm/W	0 7 4 - 7 6 5 1 1 3 ☒ R
		dark chr.	80	↓3380/↑4380 lm	129 lm/W	0 7 4 - 7 6 5 1 6 3 ☒ B
			90	↓2770/↑3580 lm	106 lm/W	0 7 4 - 7 6 5 1 1 3 ☒ B

OPAL | DIRECT / INDIRECT POWER DALI-2

SYSTEM	COLOUR TEMP.	CRI ≥	LUM. FLUX	SYSTEM	ORDER CODE
60.0 W	3000 K	80	↓3350/↑3850 lm	120 lm/W	0 7 4 - 7 6 5 1 5 3 ☒ O
		90	↓2880/↑3320 lm	103 lm/W	0 7 4 - 7 6 5 1 0 3 ☒ O
	4000 K	80	↓3810/↑4380 lm	137 lm/W	0 7 4 - 7 6 5 1 6 3 ☒ O
		90	↓3110/↑3580 lm	112 lm/W	0 7 4 - 7 6 5 1 1 3 ☒ O

Optical accessories (optional)

BLIND COVER circle 450 ceiling



COLOUR	Ø (mm)	ORDER CODE
traffic white	339	0 7 4 - 8 9 1 1 6 2 7
jet black	339	0 7 4 - 8 9 1 1 6 2 8

Order options

COLOUR	
traffic white RAL 9016	☒ 7
jet black RAL 9005	☒ 8