

MOVE IN 45 square

trimless

063-8421416M 063-8832117 002-90724



Proyecto / Tipo _____

Notas _____

Cantidad / Fecha _____



220-240V

X-PERT

UGR ≤ 10

CRI ≥ 90

X-PERT

General

Techo , Semi-empotrado

aluminio cepillado

Set de montaje blanco tráfico

IP20

1200 lm

LED

2700 K

IRC ≥ 90

L80 / 50000 h

initial MacAdam ≤ 2 SDCM

R_g: 99 , R_r: 91 , R_{t(1-15)}: 89

MR 0.53

MDER 0.48

Óptico

medium

beam angle 24°

PstLM ≤ 1.0 ¹

SVM ≤ 0.4 ¹

Eléctrico

non atenuable

15.9 W

inset 13.5 W

36 Vf

400 mA

CP2 220-240V

75 lm/W

Físico

sin borde

diameter 80 mm

height 105 mm

0.4 kg

Orificio

diameter 65 mm


min. ceiling thickness 9 mm

max. ceiling thickness 25 mm

recessed depth 180 mm

¹ Valor del producto continente a plena carga (no atenuado)


Distribución luminosa



medium 24°

h (m)	EO° (lx)	ø (m)
1	5780	0.43
2	1440	0.86
3	640	1.30
4	360	1.73
5	230	2.16

Diseño del producto



Instrucciones de montaje



Calculadora de iluminación

