

SASSO 100 square adjustable

trim

048-2730612F 048-2797318 002-90776



Proyecto / Tipo
Notas
Cantidad / Fecha



↑ IP20 ↓ IP40	220-240V	↺	X-PERT	X-PERT
------------------	----------	---	--------	--------

General

Techo , Empotrado
inclinable máx 30°
cromo
Set de montaje negro intenso
delante IP40 , detrás IP20
2330 lm

LED

4000 K
CRI ≥ 90
L80 / 50000 h
MacAdam inicial ≤ 2 SDCM
R _g : 97 , R _f : 90 , R ₍₁₋₅₎ : 89
MR 0.81
MDER 0.74

Óptico

flood
ángulo de haz 44°
UGR < 16 , ≥65° <3000 cd/m ²
P _{st} LM ≤ 1.0 ¹
SVM ≤ 0.4 ¹

Eléctrico

DALI-2
29.2 W
CP2 220-240V
80 lm/W
1 DALI Addr.

Físico


borde
longitud 118 mm
ancho 118 mm
altura 95 mm
0.52 kg

Orificio


longitud 112 mm
ancho 112 mm
espesor mín. del techo 2 mm
espesor máx. del techo 25 mm
profundidad empotrada 100 mm

¹ Valor del producto continente a plena carga (no atenuado)

Distribución luminosa



Diseño del producto



Instrucciones de montaje



Calculadora de iluminación

