

# SASSO 100 square downlight

trim 2 lamps

048-2710612M 048-2799318 002-90776



Proyecto / Tipo
Notas
Cantidad / Fecha



↑ IP20 ↓ IP44	220-240V	X-PERT	X-PERT
------------------	----------	--------	--------

## General

Techo , Empotrado
chromo
Set de montaje negro intenso
delante IP44 , detrás IP20
4340 lm

## LED

4000 K
CRI ≥ 90
L80 / 50000 h
MacAdam ≤ 2 SDCM
R <sub>g</sub> : 97 , R <sub>r</sub> : 90 , R <sub>t(1-15)</sub> : 89
MR 0.81
MDER 0.74

## Óptico

medium
ángulo de haz 34°
UGR < 16 , ≥65° <3000 cd/m²
PstLM ≤ 1.0 <sup>1</sup>
SVM ≤ 0.4 <sup>1</sup>

## Eléctrico

DALI-2
58 W
total de insertos 50 W
CP2 220-240V
75 lm/W
1 DALI Addr.

## Físico


borde
longitud 218 mm
ancho 118 mm
altura 75 mm
0.62 kg

## Orificio


longitud 210 mm
ancho 112 mm
espesor mín. del techo 2 mm
espesor máx. del techo 25 mm
profundidad empotrada 100 mm

<sup>1</sup> Valor del producto continente a plena carga (no atenuado)

## Distribución luminosa



## Diseño del producto



## Instrucciones de montaje



## Calculadora de iluminación

