

SASSO 100 square downlight

trimless

048-2710512F 048-2797117 002-90777



Proyecto / Tipo
Notas
Cantidad / Fecha



↑ IP20 ↓ IP44	220-240V	X-PERT	X-PERT
------------------	----------	--------	--------

General

Techo , Empotrado
cromo
Set de montaje blanco tráfico
delante IP44 , detrás IP20
1720 lm

LED

3000 K
CRI ≥ 90
L80 / 50000 h
MacAdam inicial ≤ 2 SDCM
R _g : 100 , R _f : 91 , R _{f(1-15)} : 88
MR 0.59
MDER 0.53

Óptico

flood
ángulo de haz 46°
UGR < 16 , ≥65° <1500 cd/m²
PstLM ≤ 1.0 ¹
SVM ≤ 0.4 ¹

Eléctrico

non atenuable
20.2 W
CP2 220-240V
85 lm/W

Físico


sin borde
longitud 105 mm
ancho 105 mm
altura 75 mm
0.53 kg

Orificio

longitud 106 mm
ancho 106 mm
espesor mín. del techo 12.5 mm
espesor máx. del techo 25 mm
profundidad empotrada 80 mm

¹ Valor del producto continente a plena carga (no atenuado)

Distribución luminosa



Diseño del producto



Instrucciones de montaje



Calculadora de iluminación

