

SASSO 100 square downlight

trim

048-2710412W 048-2797317 002-90776



Proyecto / Tipo
Notas
Cantidad / Fecha



↑ IP20 ↓ IP44	220-240V	X-PERT	X-PERT
------------------	----------	--------	--------

General

Techo , Empotrado
cromo
Set de montaje blanco tráfico
delante IP44 , detrás IP20
2230 lm

LED

2700 K
CRI ≥ 90
L80 / 50000 h
MacAdam inicial ≤ 2 SDCM
R _g : 99 , R _f : 91 , R ₍₁₋₁₅₎ : 89
MR 0.53
MDER 0.48

Óptico

wide flood
ángulo de haz 65°
≥65° <1500 cd/m ²
PstLM ≤ 1.0 ¹
SVM ≤ 0.4 ¹

Eléctrico

DALI-2
29.2 W
CP2 220-240V
76 lm/W
1 DALI Addr.

Físico


borde
longitud 118 mm
ancho 118 mm
altura 75 mm
0.52 kg

Orificio

longitud 112 mm
ancho 112 mm
espesor mín. del techo 2 mm
espesor máx. del techo 25 mm
profundidad empotrada 80 mm

¹ Valor del producto continente a plena carga (no atenuado)

Distribución luminosa



Diseño del producto



Instrucciones de montaje



Calculadora de iluminación

