

SASSO 100 round downlight

trim 2 lamps

048-2700512M 048-2798318 002-90774



Proyecto / Tipo
Notas
Cantidad / Fecha



↑ IP20 ↓ IP44	220-240V	X-PERT	X-PERT
------------------	----------	--------	--------

General

Techo , Empotrado
cromo
Set de montaje negro intenso
delante IP44 , detrás IP20
4000 lm

LED

3000 K
CRI ≥ 90
L80 / 50000 h
MacAdam inicial ≤ 2 SDCM
R _g : 100 , R _f : 91 , R _{f(1-15)} : 88
MR 0.59
MDER 0.53

Óptico

medium
ángulo de haz 33°
UGR < 16 , ≥65° <3000 cd/m²
PstLM ≤ 1.0 ¹
SVM ≤ 0.4 ¹

Eléctrico

non atenuable
58 W
total de insertos 50 W
CP2 220-240V
69 lm/W

Físico


borde
longitud 218 mm
ancho 118 mm
altura 75 mm
0.46 kg

Orificio

diámetro 105 mm
longitud 205 mm
espesor mín. del techo 2 mm
espesor máx. del techo 25 mm
profundidad empotrada 100 mm

¹ Valor del producto continente a plena carga (no atenuado)

Distribución luminosa



Diseño del producto



Instrucciones de montaje



Calculadora de iluminación

