

# TILA 22 suspended

MOVE IT 10  
030-6640639M



Proyecto / Tipo \_\_\_\_\_

Notas \_\_\_\_\_

Cantidad / Fecha \_\_\_\_\_



**General**

Techo , Barra Suspendida \_\_\_\_\_

oro rosa \_\_\_\_\_

IP20 \_\_\_\_\_

359 lm \_\_\_\_\_

inserto óptico 70 lm/W<sup>1</sup> \_\_\_\_\_

**LED**

4000 K \_\_\_\_\_

IRC ≥ 90 \_\_\_\_\_

L80 / 50000 h \_\_\_\_\_

MacAdam inicial ≤ 3 SDCM \_\_\_\_\_

R<sub>g</sub>: 97 , R<sub>f</sub>: 90 , R<sub>t(1-15)</sub>: 89 \_\_\_\_\_

MR 0.81 \_\_\_\_\_

MDER 0.74 \_\_\_\_\_

**Óptico**

medium \_\_\_\_\_

ángulo de haz 26° \_\_\_\_\_

PstLM ≤ 1.0 <sup>2</sup> \_\_\_\_\_

SVM ≤ 0.4 <sup>2</sup> \_\_\_\_\_

**Eléctrico**

DALI-2 \_\_\_\_\_

48 V \_\_\_\_\_

fijación 5.7 W \_\_\_\_\_

inserto óptico 5.1 W \_\_\_\_\_

CP3 \_\_\_\_\_

1 DALI Addr. \_\_\_\_\_


**Físico**

diámetro 22 mm \_\_\_\_\_

altura 300 mm \_\_\_\_\_


1500 mm \_\_\_\_\_

## Distribución luminosa



medium 26°		
h (m)	EO° (lx)	ø (m)
1	1740	0.46
2	440	0.92
3	190	1.37
4	110	1.83
5	70	2.29

## Diseño del producto



<sup>1</sup> incluida la consideración de las pérdidas ópticas.  
<sup>2</sup> Valor del producto continente a plena carga (no atenuado)

## Calculadora de iluminación

