

# VARO 110 S

180-6530218F



Proyecto / Tipo
Notas
Cantidad / Fecha



220-240V
X-PERT

<b>General</b>
Techo , Rail
inclinable máx 90°
rotación 355°
negro , RAL9005 <sup>1</sup>
IP20
3240 lm

<b>LED</b>
3500 K
CRI ≥ 90
MacAdam inicial ≤ 3 SDCM
R <sub>g</sub> : 97 , R <sub>f</sub> : 90 , R <sub>t(1-15)</sub> : 93
MR 0.73
MDER 0.66


<b>Óptico</b>
flood
ángulo de haz 40°

<b>Eléctrico</b>
non atenuable
23.4 W
CP2 220-240V
138 lm/W

<b>Físico</b>
diámetro 110 mm
altura 110 mm

<sup>1</sup> Código RAL


## Distribución luminosa



flood 40°

h (m)	EO° (lx)	ø (m)
1	6080	0.73
2	1520	1.46
3	680	2.18
4	380	2.91
5	240	3.64

## Diseño del producto



## Instrucciones de montaje



## Calculadora de iluminación



# VARO 110 S

180-6530218F



Proyecto / Tipo

Notas

Cantidad / Fecha

## Accesorios opticos

### HONEYCOMB LOUVER

Ø (MM)	NÚMERO(S) DE ARTÍCULO
106	080-6501118

### WIDE FLOOD LENS

Ø (MM)	NÚMERO(S) DE ARTÍCULO
106	080-6502110W

### OVAL LENS

Ø (MM)	NÚMERO(S) DE ARTÍCULO
106	080-6502210

### SNOOT

TIPO	Ø (MM)	NÚMERO(S) DE ARTÍCULO
corto	97	080-6503118
medio	97	080-6503218
ángulo	97	080-6503318

