

VARO 110 S

180-6531138M



Proyecto / Tipo
Notas
Cantidad / Fecha



220-240V
X-PERT

General
Techo , Rail
inclinable máx 90°
rotación 355°
negro , RAL9005 ¹
IP20
4480 lm

LED
4000 K
CRI ≥ 90
MacAdam inicial ≤ 3 SDCM
R _g : 100 , R _f : 92 , R _{f(1-15)} : 91
MR 0.78
MDER 0.71


Óptico
medium
ángulo de haz 25°

Eléctrico
DALI-2
36 W
CP2 220-240V
124 lm/W

Físico
diámetro 110 mm
altura 110 mm

¹ Código RAL


Distribución luminosa



medium 25°

h (m)	EO° (lx)	ø (m)
1	15500	0.45
2	3900	0.90
3	1700	1.35
4	1000	1.81
5	600	2.26

Diseño del producto



Instrucciones de montaje



Calculadora de iluminación



VARO 110 S

180-6531138M



Proyecto / Tipo

Notas

Cantidad / Fecha

Accesorios opticos

HONEYCOMB LOUVER

Ø (MM)	NÚMERO(S) DE ARTÍCULO
106	080-6501118

WIDE FLOOD LENS

Ø (MM)	NÚMERO(S) DE ARTÍCULO
106	080-6502110W

OVAL LENS

Ø (MM)	NÚMERO(S) DE ARTÍCULO
106	080-6502210

SNOOT

TIPO	Ø (MM)	NÚMERO(S) DE ARTÍCULO
corto	97	080-6503118
medio	97	080-6503218
ángulo	97	080-6503318

