

VARO 110 S

180-6531038S



Proyecto / Tipo
Notas
Cantidad / Fecha



220-240V
X-PERT

General
Techo , Rail
inclinable máx 90°
rotación 355°
negro , RAL9005 ¹
IP20
4440 lm

LED
3000 K
CRI ≥ 90
MacAdam inicial ≤ 3 SDCM
R _g : 99 , R _r : 92 , R _{t(1-15)} : 93
MR 0.61
MDER 0.55


Óptico
spot
ángulo de haz 14°

Eléctrico
DALI-2
36 W
CP2 220-240V
123 lm/W

Físico
diámetro 110 mm
altura 110 mm


¹ Código RAL

Distribución luminosa



h (m)	E0° (lx)	ø (m)
1	36600	0.25
2	9100	0.50
3	4100	0.75
4	2300	1.00
5	1500	1.25

Diseño del producto



Instrucciones de montaje



Calculadora de iluminación



VARO 110 S

180-6531038S



Proyecto / Tipo

Notas

Cantidad / Fecha

Accesorios opticos

HONEYCOMB LOUVER

Ø (MM)	NÚMERO(S) DE ARTÍCULO
106	080-6501118

WIDE FLOOD LENS

Ø (MM)	NÚMERO(S) DE ARTÍCULO
106	080-6502110W

OVAL LENS

Ø (MM)	NÚMERO(S) DE ARTÍCULO
106	080-6502210

SNOOT

TIPO	Ø (MM)	NÚMERO(S) DE ARTÍCULO
corto	97	080-6503118
medio	97	080-6503218
ángulo	97	080-6503318

