

# MINO 60 direct / indirect high lumen ceiling /

suspended system  
046-502363XZ



Proyecto / Tipo
Notas
Cantidad / Fecha



## General

Techo , Suspendido
colores especiales
IP20
indirecto 1440 lm
direct 2050 lm
total 3490 lm
4010 lm/m

## LED

4000 K
IRC $\geq 80$
L90 / 50000 h
MacAdam inicial $\leq 3$ SDCM
MR 0.72
MDER 0.65

## Óptico

Microprismatic
microprismatic
UGR $\leq 19$
PstLM $\leq 1.0$ <sup>1</sup>
SVM $\leq 0.4$ <sup>1</sup>

## Eléctrico


DALI-2
220-240 V
sistema 26.2 W
sistema 133 lm/W <sup>2</sup>
CP1
1 DALI Addr.
30 W/m

## Físico

longitud 872 mm
ancho 60 mm
altura 80 mm
2.4 kg

<sup>1</sup> Valor del producto continente a plena carga (no atenuado)  
<sup>2</sup> incluida la consideración de las pérdidas ópticas, las pérdidas de la unidad de control interno y la eficiencia del dispositivo operativo

## Distribución luminosa



## Diseño del producto



## Instrucciones de montaje



## Calculadora de iluminación

