

# MINO 60 direct / indirect high lumen ceiling /

suspended system  
046-5024637Z



|                  |  |
|------------------|--|
| Proyecto / Tipo  |  |
| Notas            |  |
| Cantidad / Fecha |  |



## General

|                                |
|--------------------------------|
| Techo , Suspendido             |
| blanco , RAL 9010 <sup>1</sup> |
| IP20                           |
| indirecto 1920 lm              |
| direct 2730 lm                 |
| total 4650 lm                  |
| 3970 lm/m                      |

## LED

|                          |
|--------------------------|
| 4000 K                   |
| IRC ≥ 80                 |
| L90 / 50000 h            |
| MacAdam inicial ≤ 3 SDCM |
| MR 0.72                  |
| MDER 0.65                |

## Óptico

|                          |
|--------------------------|
| Microprismatic           |
| microprismatic           |
| UGR ≤ 19                 |
| PstLM ≤ 1.0 <sup>2</sup> |
| SVM ≤ 0.4 <sup>2</sup>   |

## Eléctrico


|                               |
|-------------------------------|
| DALI-2                        |
| 220-240 V                     |
| sistema 34 W                  |
| sistema 137 lm/W <sup>3</sup> |
| CP1                           |
| 1 DALI Addr.                  |
| 29 W/m                        |

## Físico

|                  |
|------------------|
| longitud 1172 mm |
| ancho 60 mm      |
| altura 80 mm     |
| 3.2 kg           |

<sup>1</sup> Código RAL  
<sup>2</sup> Valor del producto continente a plena carga (no atenuado)  
<sup>3</sup> incluida la consideración de las pérdidas ópticas, las pérdidas de la unidad de control interno y la eficiencia del dispositivo operativo

## Distribución luminosa



## Diseño del producto



## Instrucciones de montaje



## Calculadora de iluminación

