

# MINO 60 high lumen

ceiling / suspended system

007-93M3517 006-16092H 046-400301G



Proyecto / Tipo
Notas
Cantidad / Fecha



## General

Techo   Suspendido
aluminio blanco   RAL 9006 <sup>1</sup>
IP20
2070 lm
2380 lm/m

## LED

3000 K
IRC ≥ 80
L90 / 50000 h
MacAdam inicial ≤ 3 SDCM
MR 0.56   MDER 0.51

## Óptico

High Performance Opal   opal (lambertsch)
PstLM ≤ 1.0 <sup>2</sup>   SVM ≤ 0.4 <sup>2</sup>

## Eléctrico

non atenuable
CP1   220-240 V
sistema 17.5 W
sistema 118 lm/W <sup>3</sup>
20 W/m

## Físico


borde
longitud 872 mm   ancho 60 mm   altura 80 mm
2.13 kg

<sup>1</sup> Código RAL

<sup>2</sup> Valor del producto continente a plena carga (no atenuado)

<sup>3</sup> incluida la consideración de las pérdidas ópticas, las pérdidas de la unidad de control interno y la eficiencia del dispositivo operativo

## Distribución luminosa



## Diseño del producto



## Instrucciones de montaje



## Calculadora de iluminación

