

MICROPRISMATIC UGR < 22

MOVE IT PRO

086-6120130 086-6020000P



| | |
|------------------|--|
| Proyecto / Tipo | |
| Notas | |
| Cantidad / Fecha | |



General

| | |
|--------------|--|
| Techo , Rail | |
| IP20 | |
| 2380 lm | |
| 1590 lm/m | |

LED

| | |
|--|--|
| 4000 K | |
| IRC ≥ 90 | |
| L90 / 50000 h | |
| MacAdam inicial ≤ 3 SDCM | |
| R _g : 99 , R _f : 92 , R ₍₁₋₁₅₎ : 90 | |
| MR 0.81 | |
| MDER 0.74 | |

Óptico

| | |
|-------------------------------|--|
| Microprismatic | |
| microprismatic | |
| PstLM ≤ 1.0 ¹ | |
| SVM ≤ 0.4 ¹ | |

Eléctrico


| | |
|------------------------------|--|
| DALI-2 | |
| 220-240 V | |
| sistema 26.4 W | |
| sistema 90 lm/W ² | |
| CP2 | |
| 1 DALI Addr. | |
| 18 W/m | |

Físico

| | |
|------------------|--|
| longitud 1500 mm | |
| ancho 43 mm | |
| altura 13 mm | |

¹ Valor del producto continente a plena carga (no atenuado)
² incluida la consideración de las pérdidas ópticas, las pérdidas de la unidad de control interno y la eficiencia del dispositivo operativo

Distribución luminosa



Diseño del producto



Calculadora de iluminación

