

# MICROPRISMATIC UGR < 22

MOVE IT PRO

086-6120030 086-6020000P



Proyecto / Tipo	
Notas	
Cantidad / Fecha	



## General

Techo , Rail	
IP20	
2210 lm	
1470 lm/m	

## LED

3000 K	
IRC ≥ 90	
L90 / 50000 h	
MacAdam inicial ≤ 3 SDCM	
R <sub>g</sub> : 99 , R <sub>f</sub> : 91 , R <sub>(1-15)</sub> : 89	
MR 0.61	
MDER 0.55	

## Óptico

Microprismatic	
microprismatic	
PstLM ≤ 1.0 <sup>1</sup>	
SVM ≤ 0.4 <sup>1</sup>	

## Eléctrico


DALI-2	
220-240 V	
sistema 26.4 W	
sistema 84 lm/W <sup>2</sup>	
CP2	
1 DALI Addr.	
18 W/m	

## Físico

longitud 1500 mm	
ancho 43 mm	
altura 13 mm	
0.73 kg	

<sup>1</sup> Valor del producto continente a plena carga (no atenuado)  
<sup>2</sup> incluida la consideración de las pérdidas ópticas, las pérdidas de la unidad de control interno y la eficiencia del dispositivo operativo

## Distribución luminosa



## Diseño del producto



## Calculadora de iluminación

