



SASSO 60 round sensor/emergency

recessed

EN Round inset (Emergency Light or Sensor); installation without tools in mounting set (trimless or with trim); surface lacquered; installation possible in different housings; LED emergency light inset: 3 variants with different test possibilities - Basic with test button, selftest with status LED or Pro DALI with monitoring via DALI; sensor with DALI-2 control: 2 variants - Basic with brightness and presence sensor or Pro with additional temperature, humidity, air quality and noise level measurement


ES Inserto redondo (luz emergencia/sensor); instalación sin herramientas mediante kit de montaje (con o sin marco); superficie lacada; posibilidad de instalar distintas carcasas; inserto luz de emerg. LED: 3 variantes con difer. opciones de test - Basic con botón de prueba, autotest con LED de estado o Pro DALI con superv. a través de DALI; sensor con control DALI-2: 2 variantes - Basic con sensor de luminosidad y presencia o Pro con medición adic. de temperatura, humedad y calidad del aire y nivel de ruido

Quickinfo

sensor
ESSENTIAL, SENSE
DALI-2

emergency light
6500 K
CRI ≥ 80
200 lm
L80 @ 50000 h
non maintained

Types



Housing colours



Inset colours



Sensors



Order options

INSET COLOUR	
○ traffic white RAL 9016	7
● jet black RAL 9005	1



BEAM ANGLE EMERGENCY LIGHT

spot lens
escape route lens
anti panic lens

Options on request

MOUNTING SET
acoustic soft ceilings

INSET COLOUR
grey, gold



SASSO 60 sensor round



ESSENTIAL SENSOR


TYPE	ORDER CODE
brightness & presence	0 48 - 2 69 3 1 1



SENSE SENSOR

TYPE	ORDER CODE
brightness, presence, temperature, sound pressure, humidity, CO ₂	0 48 - 2 69 3 1 2

SASSO 60 emergency light round



EMERGENCY 3h

TYPE	ORDER CODE
BASIC 2W	0 48 - 2 69 3 2 1
SELF-TEST 2W	0 48 - 2 69 3 2 2
PRO DALI 2W	0 48 - 2 69 3 2 3


incl. 3 interchangeable lenses

Electrical accessories


ACCUPACK

TYPE	ORDER CODE
replacement accupack 3h	0 48 - 2 69 3 9 1 0


Light distributions




emergency light
spot lens



emergency light
escape route lens



emergency light
anti panic lens



Mounting accessories

TRIMLESS MOUNTING SET for plasterboard ceilings 12.5/15/25 mm

COLOUR	ORDER CODE
○ traffic white RAL9016	0 48 - 2 69 6 1 1 7

MOUNTING SET WITH TRIM for intermediate ceilings 2-25 mm

TYPE	COLOUR	ORDER CODE
1 lamp	○ traffic white RAL9016	0 48 - 2 69 6 3 1 7
	● jet black RAL 9005	0 48 - 2 69 6 3 1 8
2 lamps	○ traffic white RAL9016	0 48 - 2 69 8 3 1 7
	● jet black RAL 9005	0 48 - 2 69 8 3 1 8

TRIMLESS MOUNTING SET for soft acoustic ceilings 25-40 mm

COLOUR	ORDER CODE
○ signal white RAL 9003	0 48 - 2 69 6 1 9 7

MOUNTING SET WITH TRIM for soft acoustic ceilings 25-40 mm

TYPE	COLOUR	ORDER CODE
1 lamp	○ signal white RAL 9003	0 48 - 2 69 6 3 9 7
	● traffic black RAL 9017	0 48 - 2 69 6 3 9 8

MOUNTING TOOL for soft acoustic ceilings

TYPE	COLOUR	ORDER CODE
SASSO 60	● traffic black RAL 9017	0 48 - 2 69 5 9 1 8

CONCRETE MOUNTING HOUSING

COLOUR	L-W-H (mm)	ORDER CODE
exposed concrete ceilings	230-230-162	0 48 - 2 69 5 2 1 0
primed concrete ceilings*	614-307-120	0 48 - 2 69 5 1 1 0

*order mounting set separately, not applicable for 2 lamps mounting set with trim