



## INO TRIPLE circle

suspended


**EN** 3 pcs. ring-shaped light fittings in rolled and seamlessly welded extruded aluminium profile; surface powder coated; pendant fitting with cable suspension; height adjustment without tools; light fitting individually height adjustable; incl. transparent feed; 3 pcs. electronic operating units installed in the canopy; completely homogeneously illuminated, satinised PMMA cover; inwards facing emission characteristics; direct/indirect illumination characteristic for additional emphasis of the ceiling and more visual comfort; energy-efficient LEDs with very good colour rendering; canopy with 2 cable openings and plug-in terminal for through wiring

**ES** 3 cuerpos de luminaria circulares fabricados de perfil de aluminio enrollado y extrusionado sin costuras de soldadura; superficie con recubrimiento de pintura en polvo; suspendido con cable; altura regulable sin herramientas; cuerpo de lámpara regulable en altura individualmente; incluido cable de alimentación transparente; 3 balastos electrónicos integrados en el remate de techo; tapa PMMA iluminada homogéneamente con acabado satinado; proyección orientada hacia el interior; iluminación directa/indirecta con un alto confort visual; LEDS de alta eficiencia que proporcionan una alta reproducción cromática; baldaquino con abertura de 2 orificios para integrar el cableado y sencilla conexión

### Quickinfo

2700 K, 3000 K, 4000 K  
CRI  $\geq$  90 / 3 SDCM  
L90 / 50000 h  
DALI-2  
High Performance Opal  
IP20

### Types



### Color



### Distribución luminosa




DiiA® standards  
251, 252, 253




direct / indirect  
illumination




tunable white  
2700 – 6500 K  
(optional)



CRI  $\geq$  98  
**XPECTRUM**  
(optional)



INO TRIPLE circle suspended



OPAL DALI-2, CRI ≥ 90

| SYSTEM  | COLOUR TEMP. | COLOUR          | LUM. FLUX | ORDER CODE              |
|---------|--------------|-----------------|-----------|-------------------------|
| 150.0 W | 2700 K       | jet black       | ↓13900 lm | 0 3 4 - 3 8 4 5 4 3 8 H |
|         |              | pure white      | ↓16500 lm | 0 3 4 - 3 8 4 5 4 3 7 H |
|         |              | special colours | ↓15200 lm | 0 3 4 - 3 8 4 5 4 3 X H |
|         |              | white aluminium | ↓15200 lm | 0 3 4 - 3 8 4 5 4 3 G H |
|         | 3000 K       | jet black       | ↓14600 lm | 0 3 4 - 3 8 4 5 5 3 8 H |
|         |              | pure white      | ↓17300 lm | 0 3 4 - 3 8 4 5 5 3 7 H |
|         |              | special colours | ↓16000 lm | 0 3 4 - 3 8 4 5 5 3 X H |
|         |              | white aluminium | ↓16000 lm | 0 3 4 - 3 8 4 5 5 3 G H |
|         | 4000 K       | jet black       | ↓15300 lm | 0 3 4 - 3 8 4 5 6 3 8 H |
|         |              | pure white      | ↓18100 lm | 0 3 4 - 3 8 4 5 6 3 7 H |
|         |              | special colours | ↓16700 lm | 0 3 4 - 3 8 4 5 6 3 X H |
|         |              | white aluminium | ↓16700 lm | 0 3 4 - 3 8 4 5 6 3 G H |

Order options

| COLOUR          |          |
|-----------------|----------|
| pure white      | RAL 9010 |
| jet black       | RAL 9005 |
| white aluminium | RAL 9006 |