


048-2641919W 048-2696198 002-90742



## Distribución luminosa



 60  
non DIM  
 120  
DALI-2  
 74  
 25  
 ø 80

## Notas

Cantidad / Fecha



Techo | Empotrado

giro  $360^\circ$ 

dorado | RAL 260-M 1

IP20

992 lm

fijación 112 lm/W<sup>2</sup>

## 2700 K

 $IRC \geq 90$ 

185 / 50

MacAdam inicia

MacAdams Initial  $\leq 5$  SDCM  
D: 101 | D: 00 | D: 88

R<sub>g</sub>: 101 | R<sub>f</sub>: 90 | R<sub>{1-15}</sub>: 88  
MR 0.51 | MDER 0.10

MR 0.51 | MDER 0.46

wallwasher floor

$$\text{PstLM} \leq 1.0^3 \mid \text{SVM} \leq 0.4^3$$

non atenuable

CP2 | 220-240 V

sistema 10.4 W | fijación 8.9 W

36 Vf | 250 mA

sin marco, para techos acústicos

diámetro 80 mm | altura 48 mm

0.29 kg

## diámetro 74-76 mm

espesor mín. del techo 25 mm | espesor máx. del  
techo 40 mm

profundidad empotrada 60 mm

<sup>1</sup> Código RAL

<sup>2</sup> incluida la consideración de las pérdidas ópticas y las pérdidas de la unidad de control interna

<sup>3</sup> Valor del producto continente a plena carga (no atenuado)