



## MITA circle 200

recessed

**EN** Ring shaped luminaire housing in die-cast aluminium; extremely slim design; recessed luminaire with trim; suitable for ceiling thickness of 2-25mm; surface powder coated; high gloss reflector with faceted design; HPO (High Performance Opal) cover for uniform illumination; energy-efficient LEDs with very good colour rendering

**ES** Cuerpo con forma de anillo y fabricado en aluminio; forma extremadamente esbelta; luminaria empotrable con marco; para instalación en techos de 2-25mm de grosor; superficie con recubrimiento de pintura en polvo; reflector de alto brillo con óptica facetada; difusor opal de alta calidad que proporciona una iluminación uniforme; LEDS de alta eficiencia que proporcionan una alta reproducción cromática

### Quickinfo

3000 K, 4000 K, tunable white  
2700 K - 6500 K  
CRI  $\geq$  80, CRI  $\geq$  90 / 3 SDCM  
UGR  $\leq$  19  
hasta 139 lm/W  
L90 / 50000 h  
DALI-2  
Opal, Reflector  
IP20

### Color



### Reflector



### Distribución luminosa





suitable for  
plasterboard or  
grid ceilings



DIN EN 12464-1  
UGR  $\leq$  19



tunable white  
2700 - 6500 K




### MITA circle 200 opal trim




#### OPAL DALI-2

| SYSTEM | COLOUR TEMP. | CRI ≥ | LUM. FLUX | SYSTEM   | ORDER CODE                                                |
|--------|--------------|-------|-----------|----------|-----------------------------------------------------------|
| 17.2 W | 3000 K       | 90    | 1550 lm   | 90 lm/W  | 0 7 4 - 8 1 2 3 0 3 <input checked="" type="checkbox"/> O |
|        | 4000 K       | 90    | 1670 lm   | 97 lm/W  | 0 7 4 - 8 1 2 3 1 3 <input checked="" type="checkbox"/> O |
| 17.5 W | 3000 K       | 80    | 1760 lm   | 101 lm/W | 0 7 4 - 8 1 2 3 5 3 <input checked="" type="checkbox"/> O |
|        | 4000 K       | 80    | 1830 lm   | 105 lm/W | 0 7 4 - 8 1 2 3 6 3 <input checked="" type="checkbox"/> O |
| 21.6 W | tunable w.   | 90    | 1820 lm   | 84 lm/W  | 0 7 4 - 8 1 2 3 D 3 <input checked="" type="checkbox"/> O |



### MITA circle 200 reflector trim



#### REFLECTOR DALI-2

| SYSTEM | COLOUR TEMP. | REFLECTOR | CRI ≥ | LUM. FLUX | SYSTEM   | ORDER CODE                                                |
|--------|--------------|-----------|-------|-----------|----------|-----------------------------------------------------------|
| 13.2 W | 3000 K       | chrome    | 90    | 1580 lm   | 120 lm/W | 0 7 4 - 8 1 2 3 0 3 <input checked="" type="checkbox"/> R |
|        |              | dark chr. | 90    | 1130 lm   | 86 lm/W  | 0 7 4 - 8 1 2 3 0 3 <input checked="" type="checkbox"/> B |
|        | 4000 K       | chrome    | 90    | 1700 lm   | 129 lm/W | 0 7 4 - 8 1 2 3 1 3 <input checked="" type="checkbox"/> R |
|        |              | dark chr. | 90    | 1220 lm   | 92 lm/W  | 0 7 4 - 8 1 2 3 1 3 <input checked="" type="checkbox"/> B |
| 13.5 W | 3000 K       | chrome    | 80    | 1800 lm   | 133 lm/W | 0 7 4 - 8 1 2 3 5 3 <input checked="" type="checkbox"/> R |
|        |              | dark chr. | 80    | 1290 lm   | 96 lm/W  | 0 7 4 - 8 1 2 3 5 3 <input checked="" type="checkbox"/> B |
|        | 4000 K       | chrome    | 80    | 1870 lm   | 139 lm/W | 0 7 4 - 8 1 2 3 6 3 <input checked="" type="checkbox"/> R |
|        |              | dark chr. | 80    | 1340 lm   | 99 lm/W  | 0 7 4 - 8 1 2 3 6 3 <input checked="" type="checkbox"/> B |
| 15.6 W | tunable w.   | chrome    | 90    | 1750 lm   | 112 lm/W | 0 7 4 - 8 1 2 3 D 3 <input checked="" type="checkbox"/> R |
|        |              | dark chr. | 90    | 1250 lm   | 80 lm/W  | 0 7 4 - 8 1 2 3 D 3 <input checked="" type="checkbox"/> B |

#### Order options

| COLOUR                 |                                       |
|------------------------|---------------------------------------|
| traffic white RAL 9016 | <input checked="" type="checkbox"/> 7 |
| jet black RAL 9005     | <input checked="" type="checkbox"/> 8 |