

048-2820417S 048-2896197 002-90752



## Notas

Cantidad / Fecha



Techo | Empotrado

inclinación máx. 30°

giro  $360^\circ$ 

blanco tráfico | RAL 9016 <sup>1</sup>

### Set de montaje blanco tráfico

parte delantera IP40 | parte trasera IP20

384 lm

fijación 75 lm/W<sup>2</sup>

## 2700 K

$$\text{IRC} \geq 9$$

1102 60  
L85 / 50

MacAdam inicia

$$B_{\tau}: 99 \mid B_{\tau}: 91 \mid B_{(1.4E)}: 89$$

MB 0.54 | MDEFB 0.49

---

MIT 6.34 | MDEL 6.43

## spot | ángulo de haz 14°

 $UGR \leq 13$ 
$$\text{PstLM} \leq 1.0^3 \mid \text{SVM} \leq 0.4^3$$

---

non atenuable

CP2 | 220-240 V

sistema 6.2 W | fijación 5.1 W

12 Vf | 450 mA


sin borde

diámetro 56 mm | altura 50 mm

## diámetro 58 mm

profundidad empotrada 140 mm

## Distribución luminosa



  
 140  
 non DIM  
 140  
 DALI-2  
 170  
 loop thr.  
 function

