

NOBA

suspended


EN Decorative suspended luminaire in aluminium; surface polished chrome, brushed aluminium or powder coated; pendant fitting with suspension, incl. feed (black or white); can be individually shortened; high quality plano-convex glass lens; no multiple shadows; energy-efficient LEDs with very good colour rendering; canopy for through wiring; converter included in canopy; ceiling mounting rings for multiple positioning of the luminaire in the room available as accessory

ES Luminaria suspendida decorativa fabricada en aluminio; superficie de cromo pulido, aluminio cepillado o recubierta por pulverización; suspendido con pendular, incl. cable de alimentación (negro o blanco); se puede acortar; lente de cristal plano-convexa alta calidad; no sombras múltiples; LEDS de alta eficiencia que proporcionan una alta reproducción cromática; baldaquino para cableado pasante; convertidor integrado en el baldaquino; anillos de montaje en techo disponibles opcionalmente para el posicionamiento múltiple de la luminaria en la sala

Quickinfo

2700 K, 3000 K, 4000 K
CRI ≥ 90
up to 130 lm/W
L90 @ 50 000 h
non DIM, DALI-2

Types




Canopy colours



Luminaire colours



Light distribution



free positioning by
cable and hook



high quality
glass lens

Order options

COLOUR TEMPERATURE

2700 K	9
3000 K	0
4000 K	1

MATERIAL COLOUR

○ traffic white RAL 9016	7
● jet black RAL 9005	8
● brushed aluminium	6
● chrome	4
● gun metal	5
● brushed brass	3
● rose gold	9

CABLE COLOUR

○ traffic white RAL 9016	7
● jet black RAL 9005	8

MATERIAL COLOUR


CANOPY/ACCESSORIES

○ traffic white RAL 9016	7
● jet black RAL 9005	8

BEAM ANGLE


wide flood 67°

NOBA suspended




NOBA 40 SUSPENDED

INSET POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
4.8 W	2700 K	726 lm	0 49-53 10::1 ■ W
36 Vf 150 mA	3000 K	755 lm	
	4000 K	790 lm	



NOBA 50 SUSPENDED

INSET POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
4.8 W	2700 K	752 lm	0 49-53 13::1 ■ W
36 Vf 150 mA	3000 K	782 lm	
	4000 K	819 lm	



NOBA 60 SUSPENDED

INSET POWER	COLOUR TEMP.	LUMINOUS FLUX	ORDER CODE
4.8 W	2700 K	765 lm	0 49-53 16::1 ■ W
36 Vf 150 mA	3000 K	796 lm	
	4000 K	833 lm	



CANOPY CEILING 220–240 V AC, 50–60 Hz, □ PC II

TYPE	EFFICIENCY	Ø-H (mm)	ORDER CODE
150 mA non DIM	η 79 %	115-29	0 05-26 0121 ■
150 mA DALI-2	η 81 %	115-29	0 05-26 0123 ■



MOUNTING SET RECESSED WITH TRIM

for installation in ceilings from 2–25 mm



TYPE	Ø-H (mm)	ORDER CODE
mounting set with trim	77-49	0 05-35 2111 ■



MOUNTING SET RECESSED TRIMLESS

for installation in plasterboard ceilings 9–25 mm



TYPE	Ø-H (mm)	ORDER CODE
mounting set trimless	75-48	0 05-35 11117



SPECIAL MOUNTING TOOL

TYPE	Ø-H (mm)	ORDER CODE
special mounting tool	100-9	0 63-89 12110

necessary to install mounting set trimless

Mounting accessories



HOOK ceiling mounted

TYPE	Ø-H (mm)	ORDER CODE
hook	16-30	0 30-10 0001 ■

Electrical accessories

POWER SUPPLY 220–240 V AC, 50–60 Hz, □ PC II

TYPE	EFFICIENCY	L-W-H (mm)	ORDER CODE
150 mA non DIM	η 80 %	93-36-25	0 02-90 810
150 mA DALI-2	η 80 %	112-29-21	0 02-90 811

*DALI-2 power supply needed

DIN RAIL COMPONENTS

TYPE	W-H-D (mm)	ORDER CODE
POWER SUPPLY 220-240 V AC	72-90-63	0 05-65 20210
160 W 48 V DC constant voltage		
LED DRIVER DALI-2 DT6 1–2 addr.	36-88-59	0 05-61 21030
200–1050 mA settable const. current		
2 × 42 W 48 V DC U _{OUT} 10–40 V		

INSET POWER is the current consumption excluding any ballast

LUMINOUS FLUX value calculated for CRI ≥ 90, colour white