

Quickinfo

3000 K, 4000 K
CRI ≥ 80 / 3 SDCM (initial MacAdam)
UGR ≤ 19, UGR ≤ 22
hasta 118 lm/W
L80 / 50000 h
DALI-2, non atenuable
front IP44, back IP20

Types



Colours

Distribución luminosa

SPADO 150 square

recessed

EN Square luminaire housing in die-cast aluminium; with trim; suitable for ceiling thickness of 2-25 mm; surface powder coated; installation without tools using snap spring closure; reflector made of polycarbonate, polished chrome; symmetric radiation characteristic; lighting level recessed; energy-efficient LEDs with very good colour rendering; external converter for ceiling insertion, for through-wiring suitable; operating device suitable for use with a central battery system

ES Cuerpo de lámpara cuadrado de fundición de aluminio; con marco; para instalación en techos de 2-25 mm de grosor; superficie con recubrimiento de pintura en polvo; sencilla instalación sin herramientas mediante un enganche elástico; reflector de policarbonato, acabado en cromo pulido; característica de emisión simétrica; lámpara retrasada; LEDS de alta eficiencia que proporcionan una alta reproducción cromática; convertidor externo para inserción en el techo, adecuado para cableado pasante; unidad de control apropiada para el funcionamiento en un sistema de batería central




DiiA® standards
251, 252, 253



glare control
(UGR ≤ 19)





splash water
protection
(IP44)



SPADO 150 square downlight trim

CRI ≥ 80 | UGR ≤ 19 | cd/m² ≤ 1500 | 220-240 V | DALI 1 ADDR. | IP20 IP44 | X-PERT | X-PERT





WIDE FLOOD 56°, traffic white, CRI ≥ 80

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
16.4 W	3000 K	1830 lm	112 lm/W	049-315157O
	4000 K	1940 lm	118 lm/W	049-315167O
27.5 W	3000 K	2990 lm	109 lm/W	049-315257O
	4000 K	3170 lm	115 lm/W	049-315267O

Mounting accessories

EXPOSED CONCRETE MOUNTING HOUSING

L·W·H (mm)	ORDER CODE
400·260·160	049-319221O

PRIMED CONCRETE MOUNTING HOUSING

L·W (mm)	ORDER CODE
310·170	049-319141O

Order options

CONTROL		COLOUR	
non DIM	1	traffic white	RAL 9016
DALI-2	3		