


Types



Distribución luminosa




UNICO Q9 basic

ceiling

EN Square surface mounted multi-downlight made of aluminium; equipped with nine individually selectable or pre-specified, customised light elements; luminaire housing can be attached to mounting plate without tools by interlock; converter integrated into luminaire housing; surface powder coated; high-quality reflector with micro-faceted, aluminum-vaporised surface; precise radiation characteristic with different symmetrical light distributions; or with asymmetric light distribution; energy-efficient high power LEDs with very good colour rendering; clank-free

ES Downlight múltiple de aluminio cuadrada de superficie; equipada con nueve sistemas de lentes elegibles individualmente o de definición fija, específicos para la aplicación; cuerpo luminoso insertable en la placa de montaje por enclavamiento y sin necesidad de herramienta; convertidor integrado en el cuerpo luminoso; superficie con recubrimiento de pintura en polvo; reflector de alta calidad con superficie de múltiples facetas revestida con aluminio por vaporización; proyección precisa con varias distribuciones de la luz distintas simétricas; o con distribución de luz asimétrica; LEDS de alta eficiencia que proporcionan una alta reproducción cromática; sin reverberación




black & chrome reflector



one luminaire multiple scenes




tunable white 2700 – 5000 K (optional)



UNICO Q9 basic high efficient ceiling

CRI ≥ 90 | 2 SDCM | UGR ≤ 19 | cd/m² ≤ 3000 | 220-240 V | 1 ADDR. | X-PERT



FLOOD ROUND 46°, CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
29.7 W	2700 K	3490 lm	118 lm/W	0 9 0 - 1 Q 9 9 ◆ C ◪ ■ 1 1
	3000 K	3490 lm	118 lm/W	0 9 0 - 1 Q 9 0 ◆ C ◪ ■ 1 1
	3500 K	3640 lm	123 lm/W	0 9 0 - 1 Q 9 2 ◆ C ◪ ■ 1 1
	4000 K	3710 lm	125 lm/W	0 9 0 - 1 Q 9 1 ◆ C ◪ ■ 1 1

WIDE FLOOD ROUND 71°, CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
29.7 W	2700 K	3590 lm	121 lm/W	0 9 0 - 1 Q 9 9 ◆ D ◪ ■ 1 1
	3000 K	3590 lm	121 lm/W	0 9 0 - 1 Q 9 0 ◆ D ◪ ■ 1 1
	3500 K	3740 lm	126 lm/W	0 9 0 - 1 Q 9 2 ◆ D ◪ ■ 1 1
	4000 K	3820 lm	129 lm/W	0 9 0 - 1 Q 9 1 ◆ D ◪ ■ 1 1

FLOOD SQUARE 54°, CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
29.7 W	2700 K	3670 lm	124 lm/W	0 9 0 - 1 Q 9 9 ◆ F ◪ ■ 1 1
	3000 K	3670 lm	124 lm/W	0 9 0 - 1 Q 9 0 ◆ F ◪ ■ 1 1
	3500 K	3820 lm	129 lm/W	0 9 0 - 1 Q 9 2 ◆ F ◪ ■ 1 1
	4000 K	3900 lm	131 lm/W	0 9 0 - 1 Q 9 1 ◆ F ◪ ■ 1 1


WIDE FLOOD SQUARE 71°, CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
29.7 W	2700 K	3770 lm	127 lm/W	0 9 0 - 1 Q 9 9 ◆ G ◪ ■ 1 1
	3000 K	3770 lm	127 lm/W	0 9 0 - 1 Q 9 0 ◆ G ◪ ■ 1 1
	3500 K	3930 lm	132 lm/W	0 9 0 - 1 Q 9 2 ◆ G ◪ ■ 1 1
	4000 K	4000 lm	135 lm/W	0 9 0 - 1 Q 9 1 ◆ G ◪ ■ 1 1



UNICO Q9 basic ceiling

CRI ≥ 90 | UGR ≤ 10 | cd/m² ≤ 1500 | 220-240 V | 1 ADDR. | X-PERT



SPOT ROUND 15°, CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
34.0 W	2700 K	2050 lm	60 lm/W	0 9 0 - 1 Q 9 4 ◆ K ◪ 0 0 1
	3000 K	2190 lm	64 lm/W	0 9 0 - 1 Q 9 5 ◆ K ◪ 0 0 1
	4000 K	2350 lm	69 lm/W	0 9 0 - 1 Q 9 6 ◆ K ◪ 0 0 1

Order options

CONTROL ◆		COLOUR ◪		REFLECTOR ■	
non DIM	1	gold dust RAL 260-M	9	chrome	0
DALI-2	3	jet black RAL 9005	B	black	B
		white aluminium RAL 9006	G		
		traffic white RAL 9016	W		

NARROW MEDIUM ROUND 22°, CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
34.0 W	2700 K	2090 lm	61 lm/W	0 9 0 - 1 Q 9 4 ⇕ N ◪ 0 0 1
	3000 K	2220 lm	65 lm/W	0 9 0 - 1 Q 9 5 ⇕ N ◪ 0 0 1
	4000 K	2390 lm	70 lm/W	0 9 0 - 1 Q 9 6 ⇕ N ◪ 0 0 1

MEDIUM ROUND 33°, CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
34.0 W	2700 K	2790 lm	82 lm/W	0 9 0 - 1 Q 9 4 ⇕ B ◪ ■ 0 1
	3000 K	2970 lm	87 lm/W	0 9 0 - 1 Q 9 5 ⇕ B ◪ ■ 0 1
	4000 K	3190 lm	94 lm/W	0 9 0 - 1 Q 9 6 ⇕ B ◪ ■ 0 1

FLOOD ROUND 49°, CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
34.0 W	2700 K	3210 lm	94 lm/W	0 9 0 - 1 Q 9 4 ⇕ C ◪ ■ 0 1
	3000 K	3420 lm	101 lm/W	0 9 0 - 1 Q 9 5 ⇕ C ◪ ■ 0 1
	4000 K	3670 lm	108 lm/W	0 9 0 - 1 Q 9 6 ⇕ C ◪ ■ 0 1

WIDE FLOOD ROUND 72°, CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
34.0 W	2700 K	3180 lm	94 lm/W	0 9 0 - 1 Q 9 4 ⇕ D ◪ ■ 0 1
	3000 K	3380 lm	99 lm/W	0 9 0 - 1 Q 9 5 ⇕ D ◪ ■ 0 1
	4000 K	3630 lm	107 lm/W	0 9 0 - 1 Q 9 6 ⇕ D ◪ ■ 0 1

MEDIUM SQUARE 32°, CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
34.0 W	2700 K	2740 lm	81 lm/W	0 9 0 - 1 Q 9 4 ⇕ E ◪ ■ 0 1
	3000 K	2920 lm	86 lm/W	0 9 0 - 1 Q 9 5 ⇕ E ◪ ■ 0 1
	4000 K	3130 lm	92 lm/W	0 9 0 - 1 Q 9 6 ⇕ E ◪ ■ 0 1

FLOOD SQUARE 56°, CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
34.0 W	2700 K	3260 lm	96 lm/W	0 9 0 - 1 Q 9 4 ⇕ F ◪ ■ 0 1
	3000 K	3470 lm	102 lm/W	0 9 0 - 1 Q 9 5 ⇕ F ◪ ■ 0 1
	4000 K	3730 lm	110 lm/W	0 9 0 - 1 Q 9 6 ⇕ F ◪ ■ 0 1

WIDE FLOOD SQUARE 71°, CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
34.0 W	2700 K	3350 lm	99 lm/W	0 9 0 - 1 Q 9 4 ⇕ G ◪ ■ 0 1
	3000 K	3570 lm	105 lm/W	0 9 0 - 1 Q 9 5 ⇕ G ◪ ■ 0 1
	4000 K	3830 lm	113 lm/W	0 9 0 - 1 Q 9 6 ⇕ G ◪ ■ 0 1

Order options

CONTROL ⇕	
non DIM	1
DALI-2	3

COLOUR ◪	
gold dust RAL 260-M	9
jet black RAL 9005	B
white aluminium RAL 9006	G
traffic white RAL 9016	W

REFLECTOR ■	
chrome	0
black	B

WALLWASHER CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
34.0 W	2700 K	2830 lm	83 lm/W	0 9 0 - 1 Q 9 4 ⇕ A ◪ 0 0 1
	3000 K	3020 lm	89 lm/W	0 9 0 - 1 Q 9 5 ⇕ A ◪ 0 0 1
	4000 K	3240 lm	95 lm/W	0 9 0 - 1 Q 9 6 ⇕ A ◪ 0 0 1

9x wallwasher


WALL FLOOR + CORRIDOR CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
34.0 W	2700 K	2910 lm	86 lm/W	0 9 0 - 1 Q 9 4 ⇕ 9 ◪ ■ 0 1
	3000 K	3110 lm	91 lm/W	0 9 0 - 1 Q 9 5 ⇕ 9 ◪ ■ 0 1
	4000 K	3330 lm	98 lm/W	0 9 0 - 1 Q 9 6 ⇕ 9 ◪ ■ 0 1


6x wallwasher floor + 3x rectangular

Planning Information


SPOT ROUND




NARROW MEDIUM ROUND




MEDIUM ROUND




FLOOD ROUND




WIDE FLOOD ROUND




MEDIUM SQUARE




FLOOD SQUARE




WIDE FLOOD SQUARE



WALL FLOOR + CORRIDOR



WALLWASHER



6x wallwasher floor
3x rectangular

Order options

CONTROL ⇕		COLOUR ◪		REFLECTOR ■	
non DIM	1	gold dust RAL 260-M	9	chrome	0
DALI-2	3	jet black RAL 9005	B	black	B
		white aluminium RAL 9006	G		
		traffic white RAL 9016	W		