



## SASSO 60 round

suspended


**EN** Cylindrical spotlight made of aluminium; surface light inset lacquered; surface housing powder coated; pendant fitting with cable suspension; incl. feed (black or white); can be individually shortened; precise radiation characteristic due to high quality lens system; COB (Chip on Board) technology for maximum efficiency; no multiple shadows; efficient LEDs with very good colour rendering; canopy for thorough wiring; converter included in canopy

**ES** Proyector cilíndrico de aluminio; superf. de inserto lumin. pintada; superf. carcasa con recubr. de polvo; suspendido con cable; incl. cable de alimentación (negro o blanco); se puede acortar; proyección precisa con óptica de lente de alta calidad; Chip on Board que proporciona una máxima eficiencia; no sombras múltiples; LEDs de eficiencia que proporcionan una alta reproducción cromática; baldaquino para cableado pasante; convertidor integrado en el baldaquino

### Quickinfo

2700 K, 3000 K, 3500 K, 4000 K  
 CRI  $\geq$  90 / 2 SDCM (initial MacAdam)  
 UGR  $\leq$  13, UGR  $\leq$  16, UGR  $\leq$  19  
 hasta 94 lm/W  
 L80 / 50000 h  
 DALI-2, non attenuable  
 IP20

### Types



### Color



### Color interno



### Distribución luminosa




glare control  
(UGR  $\leq$  16)



easy mounting  
no visible  
screws



CRI  $\geq$  95 2  
SDCM  
(optional)



## SASSO 60 round downlight suspended



### SPOT 15°, CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
10.4 W	2700 K	754 lm	73 lm/W	0 4 8 - 3 1 H 0 9 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> S
	3000 K	778 lm	75 lm/W	0 4 8 - 3 1 H 0 0 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> S
	3500 K	795 lm	76 lm/W	0 4 8 - 3 1 H 0 2 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> S
	4000 K	819 lm	79 lm/W	0 4 8 - 3 1 H 0 1 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> S

The data values for the luminous flux may differ for specific order options by -7%. Luminous flux value refers to inner colour traffic white.

### MEDIUM 26°-27°, CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
10.2 W	2700 K	888 lm	87 lm/W	0 4 8 - 3 1 H 0 9 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> M
	3000 K	921 lm	90 lm/W	0 4 8 - 3 1 H 0 0 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> M
	3500 K	941 lm	92 lm/W	0 4 8 - 3 1 H 0 2 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> M
	4000 K	961 lm	94 lm/W	0 4 8 - 3 1 H 0 1 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> M

The data values for the luminous flux may differ for specific order options by -9%. Luminous flux value refers to inner colour traffic white.

### FLOOD 40°, CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
10.2 W	2700 K	845 lm	83 lm/W	0 4 8 - 3 1 H 0 9 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> F
	3000 K	877 lm	86 lm/W	0 4 8 - 3 1 H 0 0 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> F
	3500 K	896 lm	88 lm/W	0 4 8 - 3 1 H 0 2 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> F
	4000 K	915 lm	90 lm/W	0 4 8 - 3 1 H 0 1 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> F

The data values for the luminous flux may differ for specific order options by -14%. Luminous flux value refers to inner colour traffic white.

### WIDE FLOOD 56°-57°, CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	EFFICACY	ORDER CODE
10.2 W	2700 K	887 lm	87 lm/W	0 4 8 - 3 1 H 0 9 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> W
	3000 K	920 lm	90 lm/W	0 4 8 - 3 1 H 0 0 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> W
	3500 K	941 lm	92 lm/W	0 4 8 - 3 1 H 0 2 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> W
	4000 K	961 lm	94 lm/W	0 4 8 - 3 1 H 0 1 <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> W

The data values for the luminous flux may differ for specific order options by -11%. Luminous flux value refers to inner colour traffic white.

### Order options

HEIGHT	H	CONTROL	COLOUR	INNER COLOUR
75 mm	2	non DIM	1 jet black RAL 9005	1 jet black RAL 9005
150 mm	7	DALI-2	3 traffic white RAL 9016	7 matt silver
				4 traffic white RAL 9016
				9 gold dust RAL 260-M

# James Good For You GmbH, Flums

Suiza

## Arquitecto

Daniel Huber Architektur  
GmbH

## Lighting Design

Daniel Huber Architektur  
GmbH

## Fotografía

Bruno Helbling



## Productos utilizados



**TULA suspended**



**SASSO 60 round  
suspended**



